

DRAFT

Building Works designated as Minor Works (MW) and Specified Exempted Works

**(Type A) Alteration, addition, reinstatement or removal works to existing building excluding alteration or addition to unauthorized building works**

Type A	Category I	Category II	Category III	Specified Exempted Works
(1)	Erection or alteration of internal circulation staircase —  (a) not for the use as means of escape or means of access for firefighting and rescue;  (b) not resulting in additional gross floor area;  (c) not affecting common fire resisting construction of the building; and  (d) subject to footnotes (1) & (2)			
(2)	Removal of internal circulation staircase or unauthorized internal circulation staircase not being used for means of escape or means of access for firefighting and rescue			
(3)	Formation of opening of size not more than 4.5m <sup>2</sup> in floor slab or roof slab and—			

Type A	Category I	Category II	Category III	Specified Exempted Works
	(a) not affecting common fire resisting construction of the building; and  (b) subject to footnotes (1) & (2)			
(4)	Reinstatement of approved floor slab or roof slab for an opening of size not more than 4.5 m <sup>2</sup> and not resulting in additional gross floor area			
(5)	Building works associated with installation or alteration of lifts, each having a rated load of not more than 250 kg and a car of floor area not more than 1 m <sup>2</sup> , -  (a) including associated opening of floor slab or roof slab with size not more than 4.5 m <sup>2</sup> ;  (b) not affecting common fire resisting construction of the building; and  (c) subject to footnotes (1) & (2)			
(6)	Removal of building works or unauthorized building works associated with lifts, each having a rated load of not more than 250 kg and a car of floor area not more than 1 m <sup>2</sup> , including associated construction of floor slab or roof slab with size not more than 4.5 m <sup>2</sup> .			
(7)	Building works associated with installation or alteration of stairlift and lifting platform, including			

Type A	Category I	Category II	Category III	Specified Exempted Works
	associated opening of floor slab or roof slab with size not more than 4.5 m <sup>2</sup> not affecting common fire resisting construction of the building and subject to footnotes (1) & (2)			
(8)	Removal of building works or unauthorized building works associated with stairlift and lifting platform, including associated construction of floor slab or roof slab with size not more than 4.5 m <sup>2</sup> and not resulting in additional gross floor area			
(9)	Erection or alteration of supporting structure for air-conditioning unit or water cooling tower—  (a) with weight more than 75 kg;  (b) located on suspended slab other than cantilevered slab construction; and  (c) no access is provided to the floor of the suspended slab except access for maintenance work		Erection or alteration of supporting structure for air-conditioning unit or water cooling tower –  (a) with weight not more than 75 kg;  (b) located on suspended slab other than cantilevered slab construction; and  (c) no access is provided to the floor of the suspended slab except access for maintenance work	
(10)	Erection or alteration of supporting structure of height not more than 1.5 m for air-conditioning unit or water cooling tower—  (a) with weight more than 150 kg; and		Erection or alteration of supporting structure of height not more than 1.5 m for air-conditioning unit or water cooling tower—  (a) with weight not more than 150 kg; and	

<b>Type A</b>	<b>Category I</b>	<b>Category II</b>	<b>Category III</b>	<b>Specified Exempted Works</b>
	<p>(b) located on—</p> <p>(i) suspended slab other than cantilevered slab construction, and access to the floor of the suspended slab is provided; or</p> <p>(ii) located on ground</p>		<p>(b) located on—</p> <p>(i) suspended slab other than cantilevered slab construction, and access to the floor of the suspended slab is provided; or</p> <p>(ii) located on ground</p>	
(11)	Removal of supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower supported on suspended slab of cantilevered slab construction of span more than 1 m	Removal of supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower supported on suspended slab of cantilevered slab construction of span not more than 1 m		
(12)	Removal of supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower with weight more than 1000 kg supported on suspended slab other than cantilevered slab construction	Removal of supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower with weight more than 500 kg but not more than 1000 kg supported on suspended slab other than cantilevered slab construction	<p>Removal of supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower with weight more than 150 kg but not more than 500 kg supported on suspended slab other than cantilevered slab construction</p> <p>Removal of supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower with weight more than 75 kg but not more than 150 kg supported on suspended slab other than cantilevered slab construction</p>	Removal of supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower with weight not more than 75 kg supported on roof or ground
(13)	Installation or alteration of glass reinforced polyester water tank of capacity not more than 9 m <sup>3</sup> and a water head of not more than 2 m supported on suspended slab other than cantilevered slab construction			

Type A	Category I	Category II	Category III	Specified Exempted Works
(14)			Removal of water tank or unauthorized water tank of glass reinforced polyester construction of capacity not more than 9 m <sup>3</sup>	
(15)	Alteration or replacement of protective barrier at the outer edge of balcony, verandah, staircase, landing or where there is a difference in adjacent levels more than 2 m and subject to footnote (2).	Alteration or replacement of protective barrier at the outer edge of balcony, verandah, staircase, landing or where there is a difference in adjacent levels more than 600 mm but not more than 2 m and subject to footnote (2).		
(16)	<p>Construction or alteration of fence wall with a height more than 1.8 m but not more than 3.5 m and located -</p> <p>(a) on level ground other than on suspended slab;</p> <p>(b) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(c) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high</p>	<p>Construction or alteration of fence wall with an overall height more than 1.1 m but not more than 2.5 m -</p> <p>(a) not involving construction of masonry or concrete wall with a height more than 1.8 m above the level of the ground with or without metal grille on top; and</p> <p>(b) located at one of the following geographical conditions:-</p> <p>(i) on level ground other than on suspended slab;</p> <p>(ii) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than</p>	<p>Construction or alteration of fence wall with a height not more than 1.1 m and located -</p> <p>(a) on level ground other than on suspended slab;</p> <p>(b) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(c) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high</p>	

Type A	Category I	Category II	Category III	Specified Exempted Works
		3 m high		
(17)		Removal of fence wall or unauthorized fence wall with a height more than 2.5 m but not more than 3.5 m located on ground other than on suspended slab	Removal of fence wall or unauthorized fence wall with a height more than 1.1 m but not more than 2.5 m located on ground other than on suspended slab	Removal of fence wall or unauthorized fence wall with a height not more than 1.1 m located on ground
(18)	Construction or alteration of mesh fence with a height more than 5 m but not more than 10 m and located—  (a) on level ground other than on suspended slab;  (b) at the crest of a slope with a gradient not more than 30 degrees; or  (c) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high	Construction or alteration of mesh fence with a height more than 3 m but not more than 5 m and located—  (a) on level ground other than on suspended slab;  (b) at the crest of a slope with a gradient not more than 30 degrees; or  (c) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high	Construction or alteration of mesh fence with a height not more than 3 m and located—  (a) on level ground other than on suspended slab;  (b) at the crest of a slope with a gradient not more than 30 degrees; or  (c) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high	
(19)		Removal of mesh fence or unauthorized mesh fence with a height more than 5 m but not more than 10 m located on ground other than on suspended slab	Removal of mesh fence or unauthorized mesh fence with a height more than 3 m but not more than 5 m located on ground other than on suspended slab	Removal of mesh fence or unauthorized mesh fence with a height not more than 3 m located on ground
(20)	Erection or alteration of stone panel with a panel size of more than 0.25 m <sup>2</sup> fixed to wall inside a building at a height of more than 10 m from the level of the adjoining floor	Erection or alteration of stone panel with a panel size of more than 0.25 m <sup>2</sup> fixed to wall inside a building at a height of more than 6 m but not more than 10 m from the level of the adjoining floor	Erection or alteration of stone panel with a panel size of more than 0.25 m <sup>2</sup> fixed to wall inside a building at a height of more than 3 m but not more than 6 m from the level of the adjoining floor	
(21)			Erection or alteration of stone panel	

Type A	Category I	Category II	Category III	Specified Exempted Works
			with a panel size of more than 0.25 m <sup>2</sup> fixed to the exterior of external wall of a building at a height of not more than 6 m from the level of the adjoining floor and projecting not more than 300 mm from the external wall	
(22)		<p>Construction, alteration or replacement of window involving the main frame not resulting in additional load to cantilevered slab construction where the highest point of the window is at a height of --</p> <p>(a) not more than 100 m above the level of the ground;</p> <p>(b) more than 100 m above the level of the ground with the area of the external wall opening not more than 6 m<sup>2</sup>; or</p> <p>(c) more than 100 m above the level of the ground with the least dimension of the external wall opening not more than 1.8 m</p>	<p>Alteration or replacement of window involving sub-frame where the highest point of the window is at a height of –</p> <p>(a) not more than 100 m above the level of the ground;</p> <p>(b) more than 100 m above the level of the ground with the area of the external wall opening not more than 6 m<sup>2</sup>; or</p> <p>(c) more than 100 m above the level of the ground with the least dimension of the external wall opening not more than 1.8 m</p> <p>Alteration or replacement of window involving openable sash</p>	
(23)			<p>Construction or alteration of glass façade—</p> <p>(a) with a height not more than 6 m at ground floor level;</p> <p>(b) not affecting common fire resisting construction of the building; and</p>	

Type A	Category I	Category II	Category III	Specified Exempted Works
			(c) subject to footnote (2)	
(24)			Removal of glass façade or unauthorized glass façade with a height not more than 6 m at ground floor level	
(25)	<p>Construction of spread footing associated with minor works –</p> <ul style="list-style-type: none"> <li>(a) with maximum bearing capacity of 100 kPa;</li> <li>(b) with excavation of depth not more than 3 m;</li> <li>(c) not located within Area Number 1 or 3 of the Scheduled Areas as specified in the Fifth Schedule of the Buildings Ordinance; and</li> <li>(d) located at one of the following geographical conditions: <ul style="list-style-type: none"> <li>(i) on level ground other than on suspended slab;</li> <li>(ii) at the crest of a slope with a gradient not more than 30 degrees; or</li> <li>(iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high</li> </ul> </li> </ul>			

<b>Type A</b>	<b>Category I</b>	<b>Category II</b>	<b>Category III</b>	<b>Specified Exempted Works</b>
(26)	Excavation works of depth more than 2.5 m but not more than 3 m associated with minor works and not located within Area Number 1 or 3 of the Scheduled Areas as specified in the Fifth Schedule of the Buildings Ordinance	Excavation works of depth more than 1.2 m but not more than 2.5 m associated with minor works and not located within Area Number 1 or 3 of the Scheduled Areas as specified in the Fifth Schedule of the Buildings Ordinance	Excavation works of depth not more than 1.2 m associated with minor works and not located within Area Number 1 or 3 of the Scheduled Areas as specified in the Fifth Schedule of the Buildings Ordinance	
(27)	<p>Construction or alteration of radio base station for telecommunication services i.e. a structure for housing telecommunication equipment, within or on rooftop, where-</p> <p>(a) the maximum overall size of the structure is not more than 4.5 m x 4.5 m x 3.2 m (length x width x height) ;</p> <p>(b) the structure is located at a height not more than 100 m above the level of the ground;</p> <p>(c) the works do not affect common means of escape of the building; and</p> <p>(d) subject to footnote (2)</p>			
(28)		<p>Removal of radio base station for telecommunication services in the form of enclosure or cabinet together with supporting structure within or on rooftop, where-</p> <p>(a) the maximum overall size of the base station shelter is not more than 4.5 m x 4.5 m x</p>		

Type A	Category I	Category II	Category III	Specified Exempted Works
		<p>3.2 m (length x width x height) ; and</p> <p>(b) the structure is located at a height of not more than 100 m above the level of the ground</p>		
(29)	<p>Building works associated with the construction or alteration of radio base station for telecommunication services in the form of antenna and transceiver only, where –</p> <p>(a) the size of the antenna or transceiver is not more than 600 mm x 600 mm x 2.5 m (width x depth x height);</p> <p>(b) it is located on the roof;</p> <p>(c) the works do not affect common means of escape of the building; and</p> <p>(d) subject to footnote (2)</p>		<p>Building works associated with the construction or alteration of radio base station for telecommunication services in the form of antenna and transceiver only, where –</p> <p>(a) the size of the antenna or transceiver is not more than 500 mm x 500 mm x 700 mm (width x depth x height);</p> <p>(b) the load imposed is not more than 100 kg on any one beam or slab;</p> <p>(c) the antenna or pole do not project beyond the external wall;</p> <p>(d) the works do not affect common means of escape of the building; and</p> <p>(e) subject to footnote (2)</p>	
(30)			<p>Removal of building works / unauthorized building works associated with radio base station for telecommunication services in the form of antenna and transceiver only</p>	

Footnote:

- (1) Works not involving any removal, with or without subsequent reinstatement, of approved structural elements except:
  - (a) simply supported beams not of prestressed construction;
  - (b) simply supported beams not supporting any columns;
  - (c) openings in slabs not of prestressed construction ; or
  - (d) openings in slabs supported by beams all round.
  
- (2) Works not resulting in additional load to cantilevered slab construction

**(TYPE B) Removal of building works (including unauthorized building works) to existing building and associated reinstatement works**

<b>Type B</b>	<b>Category I</b>	<b>Category II</b>	<b>Category III</b>	<b>Specified Exempted Works</b>
(1)	Internal circulation staircase or unauthorized internal circulation staircase not being used for means of escape or means of access for firefighting and rescue			
(2)	Building works or unauthorized building works associated with a lift, each having a rated load of not more than 250 kg and a car of floor area not more than 1 m <sup>2</sup> , including associated construction of floor slab or roof slab with size not more than 4.5 m <sup>2</sup>			
(3)	Building works or unauthorized building works associated with stairlift and lifting platform, including associated construction of floor slab or roof slab with size not more than 4.5 m <sup>2</sup> and not resulting in additional gross floor area			
(4)	Supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower supported on suspended slab of cantilevered slab construction of span more than 1 m	Supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower supported on suspended slab of cantilevered slab construction of span not more than 1 m		
(5)	Supporting structure or unauthorized supporting structure for air-	Supporting structure or unauthorized supporting structure for air-	Supporting structure or unauthorized supporting structure for air-	Supporting structure or unauthorized supporting structure for air-

<b>Type B</b>	<b>Category I</b>	<b>Category II</b>	<b>Category III</b>	<b>Specified Exempted Works</b>
	conditioning unit or water cooling tower with weight more than 1000 kg supported on suspended slab other than cantilevered slab construction	conditioning unit or water cooling tower with weight more than 500 kg but not more than 1000 kg supported on suspended slab other than cantilevered slab construction	conditioning unit or water cooling tower with weight more than 150 kg but not more than 500 kg supported on suspended slab other than cantilevered slab construction  Supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower with weight more than 75 kg but not more than 150 kg supported on suspended slab other than cantilevered slab construction	conditioning unit or water cooling tower with weight not more than 75 kg supported on roof or ground
(6)			Water tank or unauthorized water tank of glass reinforced polyester construction of capacity not more than 9 m <sup>3</sup>	
(7)		Fence wall or unauthorized fence wall with a height more than 2.5 m but not more than 3.5 m located on ground other than on suspended slab	Fence wall or unauthorized fence wall with an overall height more than 1.1 m but not more than 2.5 m located on ground other than on suspended slab	Fence wall or unauthorized fence wall with a height not more than 1.1 m located on ground
(8)		Mesh fence or unauthorized mesh fence with a height more than 5 m but not more than 10 m located on ground other than on suspended slab	Mesh fence or unauthorized mesh fence with a height more than 3 m but not more than 5 m located on ground other than on suspended slab	Mesh fence or unauthorized mesh fence with a height not more than 3 m located on ground
(9)			Glass façade or unauthorized glass facade with a height not more than 6 m at ground floor level	
(10)		Radio base station or unauthorized		

Type B	Category I	Category II	Category III	Specified Exempted Works
		<p>radio base station for telecommunication services in the form of enclosure or cabinet together with supporting structure within or on rooftop, where-</p> <p>(a) the maximum overall size of the base station shelter is not more than 4.5 m x 4.5 m x 3.2 m (length x width x height) ; and</p> <p>(b) the shelter is located at a height of not more than 100 m above the level of the ground</p>		
(11)			<p>Building works or unauthorized building works associated with radio base station for telecommunication services in the form of antenna and transceiver only</p>	
(12)	<p>Drainage works or unauthorized drainage works -</p> <p>(a) involving excavation of depth more than 2.5 m but not more than 3 m;</p> <p>(b) not involving excavation in Area No. 1 or 3 of the Scheduled Areas specified in the Fifth Schedule of the Buildings Ordinance; and</p> <p>(c) located at one of the following geographical conditions:-</p>	<p>Drainage works or unauthorized drainage works -</p> <p>(a) involving excavation of depth more than 1.2 m but not more than 2.5 m;</p> <p>(b) not involving excavation in Area No. 1 or 3 of the Scheduled Areas specified in the Fifth Schedule of the Buildings Ordinance; and</p> <p>(c) located at one of the following geographical conditions:-</p>	<p>Drainage works or unauthorized drainage works -</p> <p>(a) involving excavation of depth not more than 1.2 m;</p> <p>(b) not involving excavation in Area No. 1 or 3 of the Scheduled Areas specified in the Fifth Schedule of the Buildings Ordinance; and</p> <p>(c) located at one of the following geographical conditions:-</p> <p>(i) on level ground other than</p>	

<b>Type B</b>	<b>Category I</b>	<b>Category II</b>	<b>Category III</b>	<b>Specified Exempted Works</b>
	<p>(i) on level ground other than on suspended slab; or</p> <p>(ii) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high</p>	<p>(i) on level ground other than on suspended slab; or</p> <p>(ii) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high</p>	<p>on suspended slab; or</p> <p>(ii) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high</p>	
(13)	<p>Signboard or unauthorized signboard projecting from external wall having –</p> <p>(a) a display area<sup>#</sup> between 10 m<sup>2</sup> to 20 m<sup>2</sup>; and</p> <p>(b) projection not more than 4.2 m from the external wall</p>	<p>Signboard or unauthorized signboard projecting from external wall having –</p> <p>(a) a display area<sup>#</sup> more than 1 m<sup>2</sup> but not more than 10 m<sup>2</sup>; and</p> <p>(b) projection not more than 4.2 m from the external wall</p>	<p>Signboard or unauthorized signboard projecting from external wall having –</p> <p>(a) a display area<sup>#</sup> not more than 1 m<sup>2</sup>;</p> <p>(b) projection more than 600 mm but not more than 1 m from the external wall; and</p> <p>(c) the highest point of the signboard at a height of more than 6 m above the level of the ground</p> <p>Signboard including unauthorized signboard having –</p> <p>(a) a display area<sup>#</sup> not more than 1 m<sup>2</sup>;</p>	

Type B	Category I	Category II	Category III	Specified Exempted Works
			<p>(b) projection more than 600 mm but not more than 1 m from the external wall; and</p> <p>(c) the highest point of the signboard at a height of not more than 6 m above the level of the ground</p>	
(14)	Signboard or unauthorized signboard located at the rooftop of a building having a display area <sup>#</sup> between 10 m <sup>2</sup> to 20 m <sup>2</sup>	Signboard or unauthorized signboard located at the rooftop of a building having a display area <sup>#</sup> not more than 10 m <sup>2</sup>		
(15)	<p>Signboard or unauthorized signboard affixed to the external wall having–</p> <p>(a) a display area<sup>#</sup> between 10 m<sup>2</sup> to 40 m<sup>2</sup>; and</p> <p>(b) projection not more than 600 mm from the external wall</p>		<p>Signboard or unauthorized signboard affixed to the external wall having –</p> <p>(a) a display area<sup>#</sup> not more than 10 m<sup>2</sup>;</p> <p>(b) projection not more than 600 mm from the external wall; and</p> <p>(c) the highest point of the signboard at a height of more than 6 m above the level of the ground</p> <p>Signboard including unauthorized signboard affixed to the external wall having –</p>	

Type B	Category I	Category II	Category III	Specified Exempted Works
			<p>(a) a display area<sup>#</sup> not more than 5 m<sup>2</sup> with a height not more than 1 m;</p> <p>(b) projection not more than 600 mm from the external wall; and</p> <p>(c) the highest point of the signboard at a height of not more than 6 m above the level of the ground</p>	
(16)			<p>Signboard or unauthorized signboard in the form of individual character, letter, logo, graphic or symbol supported independently-</p> <p>(a) each with a display area<sup>#</sup> not more than 1 m<sup>2</sup>; and</p> <p>(b) the highest point of the signboard being at a height of more than 6 m above the level of the ground</p> <p>Signboard or unauthorized signboard in the form of individual character, letter, logo, graphic or symbol supported independently -</p> <p>(a) each with a display area<sup>#</sup> not more than 1 m<sup>2</sup>; and</p>	<p>Signboard or unauthorized signboard in the form of individual character, letter, logo, graphic or symbol supported independently-</p> <p>(a) each with a display area<sup>#</sup> not more than 1 m<sup>2</sup>; and</p> <p>(b) the highest point of the signboard being at a height of not more than 3 m above the level of the ground</p>

Type B	Category I	Category II	Category III	Specified Exempted Works
			(b) the highest point of the signboard being at a height of more than 3 m but not more than 6 m above the level of the ground	
(17)			<p>Signboard or unauthorized signboard located on or hung underneath the soffit of a balcony or canopy not being a cantilevered slab construction having –</p> <p>(a) a display area<sup>#</sup> not more than 1 m<sup>2</sup> ; and</p> <p>(b) a vertical dimension not more than 1 m</p>	
(18)			<p>Signboard or unauthorized signboard in cylindrical, sculptural, non-planar or other free-form or which is substantially three-dimensional, having –</p> <p>(a) the largest size not more than 600 mm x 600 mm x 600 mm (length x width x height); and</p> <p>(b) projection not more than 1 m from the external wall</p>	
(19)			<p>Signboard or unauthorized signboard which is free-standing and having –</p> <p>(a) a display area<sup>#</sup> not more than</p>	

Type B	Category I	Category II	Category III	Specified Exempted Works
			<p>20 m<sup>2</sup> ; and</p> <p>(b) the highest point of the signboard at a height not more than 6 m from the level of the ground</p>	
(20)	Chimney or unauthorized chimney with least cross-sectional dimension more than 500 mm attached to external wall	Chimney or unauthorized chimney with least cross-sectional dimension not more than 500 mm attached to external wall		
(21)			<p>Canopy excluding concrete construction, projecting more than 750 mm but not more than 2 m from the external wall over the main entrance of a building</p> <p>Architectural projection, canopy hood, rack other than drying rack-</p> <p>(a) projecting not more than 750 mm from the external wall of a building; and</p> <p>(b) not involving concrete construction</p>	
(22)			Drying rack or unauthorized drying rack projecting from the external wall	
(23)		<p>Supporting frame or unauthorized supporting frame for air-conditioning unit –</p> <p>(a) projecting more than 750 mm from the external wall; and</p>	<p>Supporting frame or unauthorized supporting frame for air-conditioning unit –</p> <p>(a) projecting not more than 750 mm from the external wall;</p>	

Type B	Category I	Category II	Category III	Specified Exempted Works
		(b) not involving concrete construction	and (b) not involving concrete construction	
(24)	Unauthorized structures affixed to canopy or balcony of cantilevered slab construction of span more than 1 m	Unauthorized structure affixed to canopy or balcony of cantilevered slab construction of span not more than 1 m		
(25)	Unauthorized structure projecting more than 2 m from the external wall	Unauthorized structure projecting more than 750 mm but not more than 2 m from the external wall	Unauthorized structure projecting not more than 750 mm from the external wall	
(26)	Unauthorized structure affixed to canopy or balcony other than cantilevered slab construction of span not more than 2 m	Unauthorized structure affixed to canopy or balcony other than cantilevered slab construction of span more than 1 m but not more than 2 m	Unauthorized structure affixed to canopy or balcony other than cantilevered slab construction of span not more than 1 m	
(27)			Unauthorized structure affixed to canopy or balcony other than cantilevered slab construction involving the following only -  (a) shopfront projection;  (b) false ceiling construction; or  (c) window enclosure	
(28)	Unauthorized two-storey structure on suspended slab other than canopy or balcony satisfying the following criteria-	Unauthorized single storey structure on suspended slab other than canopy or balcony satisfying the following criteria -	Unauthorized single storey structure on ground satisfying the following criteria -	

Type B	Category I	Category II	Category III	Specified Exempted Works
	(a) structure not more than 10 m above adjacent floor level; (b) structure of roofed over area not more than 30 m <sup>2</sup> ; (c) structural element has a clear span not more than 6 m or a cantilevered slab not more than 1 m; (d) structure which is not of pre-stressed concrete construction; and (e) works not involving alteration or demolition of approved structural elements	(a) structure not more than 5 m above adjacent floor level; (b) structure of roofed over area not more than 30 m <sup>2</sup> ; (c) structural element has a clear span not more than 6 m or a cantilevered slab not more than 1 m; (d) structure which is not of pre-stressed concrete construction; and (e) works not involving alteration or demolition of approved structural elements	(a) structure not more than 5 m above adjacent ground; (b) structure of roofed over area not more than 30 m <sup>2</sup> ; (c) structural element has a clear span not more than 6 m or a cantilevered slab not more than 1 m; (d) structure which is not of pre-stressed concrete construction; and (e) works not involving alteration or demolition of approved structural elements	
(29)	Unauthorized floor slab			

# “display area” means a planar area on the signboard for display of the advertising message or any other information such as name, registered trade mark or nature of the trade or business in the form of any word, letter, character, figure, symbol, notice or sign printed, painted, carved, engraved or otherwise shown either on plastic or canvas sheet, steel or timber plate, television screen, light emitting diode or plasma screens

**(Type C) Drainage works in or for existing building and installation or alteration of water tank**

<b>Type C</b>	<b>Category I</b>	<b>Category II</b>	<b>Category III</b>	<b>Specified Exempted Works</b>
(1)	Repair of underground drainage works involving excavation of depth more than 2.5 m but not more than 3 m and— (a) subject to footnote (2); and (b) located at one of the following geographical conditions:- (i) on level ground other than on suspended slab; (ii) at the crest of a slope with a gradient not more than 30 degrees; or (iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high	Repair of underground drainage works involving excavation of depth more than 1.2 m but not more than 2.5 m and— (a) subject to footnote (2); and (b) located at one of the following geographical conditions:- (i) on level ground other than on suspended slab; (ii) at the crest of a slope with a gradient not more than 30 degrees; or (iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high	Repair of underground drainage works involving excavation of depth not more than 1.2 m and— (a) subject to footnote (2); and (b) located at one of the following geographical conditions:- (i) on level ground other than on suspended slab; (ii) at the crest of a slope with a gradient not more than 30 degrees; or (iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high	
(2)	Addition or alteration of underground drainage works— (a) not involving alteration of disconnecting trap; (b) involving excavation of depth more than 2.5 m but not more than 3 m; (c) subject to footnotes (2); and	Addition or alteration of underground drainage works— (a) not involving alteration of disconnecting trap; (b) involving excavation of depth more than 1.2 m but not more than 2.5 m; (c) subject to footnotes (2); and	Addition or alteration of underground drainage works— (a) not involving alteration of disconnecting trap; (b) involving excavation of depth more than 1.2 m; (c) subject to footnotes (2); and	

Type C	Category I	Category II	Category III	Specified Exempted Works
	<p>(d) located at one of the following geographical conditions:-</p> <p>(i) on level ground other than on suspended slab;</p> <p>(ii) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high</p>	<p>(d) located at one of the following geographical conditions:-</p> <p>(i) on level ground other than on suspended slab;</p> <p>(ii) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high</p>	<p>(d) located at one of the following geographical conditions:-</p> <p>(i) on level ground other than on suspended slab;</p> <p>(ii) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high</p>	
(3)		Addition, alteration or repair of aboveground drainage works involving embedded piping and subject to footnote (1)		
(4)			Addition or alteration of aboveground drainage works not involving embedded piping and subject to footnote (1)	
(5)			Addition or alteration of aboveground drainage works involving communal piping and subject to footnote (1)	
(6)	<p>Removal of unauthorized drainage works –</p> <p>(a) involving excavation of depth more than 2.5 m but not more than 3 m;</p>	<p>Removal of unauthorized drainage works –</p> <p>(a) involving excavation of depth more than 1.2 m but not more than 2.5 m;</p>	<p>Removal of unauthorized drainage works –</p> <p>(a) involving excavation of depth not more than 1.2 m;</p> <p>(b) subject to footnote (2); and</p>	

Type C	Category I	Category II	Category III	Specified Exempted Works
	<p>(b) subject to footnote (2); and</p> <p>(c) located at one of the following geographical conditions:-</p> <p>(i) on level ground other than on suspended slab;</p> <p>(ii) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high</p>	<p>(b) subject to footnote (2); and</p> <p>(c) located at one of the following geographical conditions:-</p> <p>(i) on level ground other than on suspended slab;</p> <p>(ii) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high</p>	<p>(c) located at one of the following geographical conditions:-</p> <p>(i) on level ground other than on suspended slab;</p> <p>(ii) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(iii) not less than 5 m from the edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high</p>	
(7)	<p>Installation or alteration of glass reinforced polyester water tank of capacity not more than 9 m<sup>3</sup> and a water head of not more than 2 m supported on suspended slab other than cantilevered slab construction</p>		<p>Removal of water tank or unauthorized water tank of glass reinforced polyester construction of capacity not more than 9 m<sup>3</sup></p>	

Footnote:

- (1) Works not resulting in additional load to cantilevered slab construction
- (2) Works not involving excavation in Area No. 1 or 3 of the Scheduled Areas specified in the Fifth Schedule of the Buildings Ordinance

**(Type D) Signboard including associated building works**

<b>Type D</b>	<b>Category I</b>	<b>Category II</b>	<b>Category III</b>	<b>Specified Exempted Works</b>
(1)	<p>Erection or alteration of signboard projecting from external wall having –</p> <p>(a) a display area<sup>#</sup> between 10 m<sup>2</sup> to 20 m<sup>2</sup>;</p> <p>(b) projection more than 600 mm but not more than 4.2 m from the external wall; and</p> <p>(c) the works subject to footnotes (1) and (2)</p>	<p>Erection or alteration of signboard projecting from external wall having –</p> <p>(a) a display area<sup>#</sup> more than 1 m<sup>2</sup> but not more than 10 m<sup>2</sup>;</p> <p>(b) projection more than 600 mm but not more than 4.2 m from the external wall; and</p> <p>(c) the works subject to footnotes (1) and (2)</p>	<p>Erection or alteration of signboard projecting from external wall having –</p> <p>(a) a display area<sup>#</sup> not more than 1 m<sup>2</sup>;</p> <p>(b) projection more than 600 mm but not more than 1 m from the external wall;</p> <p>(c) the highest point of the signboard at a height of more than 6 m above the level of the ground; and</p> <p>(d) the works subject to footnotes (1) and (2)</p> <p>Erection or alteration of signboard projecting from external wall having –</p> <p>(a) a display area<sup>#</sup> not more than 1 m<sup>2</sup>;</p> <p>(b) projection more than 600 mm but not more than 1 m from the external wall;</p> <p>(c) the highest point of the signboard at a height of not</p>	

Type D	Category I	Category II	Category III	Specified Exempted Works
			<p>more than 6 m above the level of the ground; and</p> <p>(d) the works subject to footnotes (1) and (2)</p>	
(2)	<p>Removal of signboard or unauthorized signboard projecting from external wall having</p> <p>(a) a display area<sup>#</sup> between 10 m<sup>2</sup> to 20 m<sup>2</sup>; and</p> <p>(b) projection not more than 4.2 m from the external wall</p>	<p>Removal of signboard or unauthorized signboard projecting from external wall having</p> <p>(a) a display area<sup>#</sup> more than 1 m<sup>2</sup> but not more than 10 m<sup>2</sup>; and</p> <p>(b) projection not more than 4.2 m from the external wall</p>	<p>Removal of signboard or unauthorized signboard projecting from external wall having –</p> <p>(a) a display area<sup>#</sup> not more than 1 m<sup>2</sup>;</p> <p>(b) projection more than 600 mm but not more than 1 m from the external wall; and</p> <p>(c) the highest point of the signboard at a height of more than 6 m above the level of the ground</p> <p>Removal of signboard including unauthorized signboard having –</p> <p>(a) a display area<sup>#</sup> not more than 1 m<sup>2</sup>;</p> <p>(b) projection more than 600 mm but not more than 1 m from the external wall; and</p> <p>(c) the highest point of the signboard at a height of not more than 6 m above the level of the ground</p>	

<b>Type D</b>	<b>Category I</b>	<b>Category II</b>	<b>Category III</b>	<b>Specified Exempted Works</b>
(3)	Erection or alteration of signboard located at the rooftop of a building—  (a) having a display area <sup>#</sup> between 10 m <sup>2</sup> to 20 m <sup>2</sup> ;  (b) not projecting beyond the external wall; and  (c) subject to footnote (1)	Erection or alteration of signboard located at the rooftop of a building—  (a) having a display area <sup>#</sup> not more than 10 m <sup>2</sup> ;  (b) not projecting beyond the external wall; and  (c) subject to footnote (1)		
(4)	Removal of signboard or unauthorized signboard located at the rooftop of a building having a display area <sup>#</sup> between 10 m <sup>2</sup> to 20 m <sup>2</sup>	Removal of signboard or unauthorized signboard located at the rooftop of a building having a display area <sup>#</sup> not more than 10 m <sup>2</sup>		
(5)	Erection or alteration of signboard affixed to the external wall having—  (a) a display area <sup>#</sup> between 10 m <sup>2</sup> to 40 m <sup>2</sup> ;  (b) projection not more than 600 mm from the external wall;  (c) a clear space of not less than 2.5 m beneath every part of the signboard above the level of the ground; and  (d) the works subject to footnote (1)	Erection or alteration of signboard affixed to the external wall having—  (a) a display area <sup>#</sup> not more than 10 m <sup>2</sup> ;  (b) projection not more than 600 mm from the external wall;  (c) a clear space of not less than 2.5 m beneath every part of the signboard above the level of the ground; and  (d) the works subject to footnote (1)	Erection or alteration of signboard affixed to the external wall having -  (a) a display area <sup>#</sup> not more than 10 m <sup>2</sup> with a height not more than 1 m;  (b) projection not more than 600 mm from the external wall;  (c) a clear space of not less than 2.5 m beneath every part of the signboard above the level of the ground;  (d) the highest point of the signboard at a height of more	

Type D	Category I	Category II	Category III	Specified Exempted Works
			<p>than 6 m above the level of the ground; and</p> <p>(e) the works subject to footnote (1)</p> <p>Erection or alteration of signboard affixed to the external wall having –</p> <p>(a) a display area<sup>#</sup> not more than 5 m<sup>2</sup> with a height not more than 1 m;</p> <p>(b) projection not more than 600 mm from the external wall;</p> <p>(c) a clear space of not less than 2.5 m beneath every part of the signboard above the level of the ground;</p> <p>(d) the highest point of the signboard at a height of not more than 6 m above the level of the ground; and</p> <p>(e) the works subject to footnotes (1)</p>	
(6)	<p>Removal of signboard or unauthorized signboard affixed to the external wall having–</p> <p>(a) a display area<sup>#</sup> between 10 m<sup>2</sup> to 40 m<sup>2</sup>; and</p>		<p>Removal of signboard or unauthorized signboard affixed to the external wall having -</p> <p>(a) a display area<sup>#</sup> not more than 10 m<sup>2</sup>;</p>	

Type D	Category I	Category II	Category III	Specified Exempted Works
	(b) projection not more than 600 mm from the external wall		<p>(b) projection not more than 600 mm from the external wall; and</p> <p>(c) the highest point of the signboard at a height of more than 6 m above the level of the ground</p> <p>Removal of signboard including unauthorized signboard affixed to the external wall having –</p> <p>(a) a display area<sup>#</sup> not more than 5 m<sup>2</sup> with a height not more than 1 m;</p> <p>(b) projection not more than 600 mm from the external wall; and</p> <p>(c) the highest point of the signboard at a height of not more than 6 m above the level of the ground</p>	
(7)			<p>Erection or alteration of signboard in the form of individual character, letter, logo, graphic or symbol supported independently –</p> <p>(a) each with a display area<sup>#</sup> not more than 1 m<sup>2</sup>;</p> <p>(b) projection or thickness being not more than 150 mm from the external wall;</p>	<p>Erection or alteration of signboard in the form of individual character, letter, logo, graphic or symbol supported independently –</p> <p>(a) each with a display area<sup>#</sup> not more than 1 m<sup>2</sup>;</p> <p>(b) projection or thickness being not more than 150 mm from the external wall;</p>

Type D	Category I	Category II	Category III	Specified Exempted Works
			<p>(c) the highest point of the signboard being at a height of more than 6 m above the level of the ground;</p> <p>(d) each not being erected on a common sign structure; and</p> <p>(e) the works subject to footnote (1)</p> <p>Erection or alteration of signboard in the form of individual character, letter, logo, graphic or symbol supported independently –</p> <p>(a) each with a display area<sup>#</sup> not more than 1 m<sup>2</sup>;</p> <p>(b) projection or thickness being not more than 150 mm from the external wall;</p> <p>(c) the highest point of the signboard being at a height of more than 3 m but not more than 6 m above the level of the ground;</p> <p>(d) each not being erected on a common sign structure; and</p> <p>(e) the works subject to footnote (1)</p>	<p>(c) the highest point of the signboard being at a height of not more than 3 m above the level of the ground;</p> <p>(d) each not being erected on a common sign structure; and</p> <p>(e) the works subject to footnote (1)</p>
(8)			Removal of signboard or	Removal of signboard or

Type D	Category I	Category II	Category III	Specified Exempted Works
			<p>unauthorized signboard in the form of individual character, letter, logo, graphic or symbol supported independently –</p> <p>(a) each with a display area<sup>#</sup> not more than 1 m<sup>2</sup>; and</p> <p>(b) the highest point of the signboard being at a height of more than 6 m above the level of the ground</p> <p>Removal of signboard or unauthorized signboard in the form of individual character, letter, logo, graphic or symbol supported independently –</p> <p>(a) each with a display area<sup>#</sup> not more than 1 m<sup>2</sup>; and</p> <p>(b) the highest point of the signboard being at a height of more than 3 m but not more than 6 m above the level of the ground</p>	<p>unauthorized signboard in the form of individual character, letter, logo, graphic or symbol supported independently –</p> <p>(a) each with a display area<sup>#</sup> not more than 1 m<sup>2</sup>; and</p> <p>(b) the highest point of the signboard being at a height of not more than 3 m above the level of the ground</p>
(9)			<p>Erection or alteration of signboard located on or hung underneath the soffit of a balcony or canopy not being a cantilevered slab construction having –</p> <p>(a) a display area<sup>#</sup> not more than 1 m<sup>2</sup>; and</p>	

Type D	Category I	Category II	Category III	Specified Exempted Works
			(b) a vertical dimension not more than 1 m	
(10)			<p>Removal of signboard or unauthorized signboard located on or hung underneath the soffit of a balcony or canopy not being a cantilevered slab construction having –</p> <p>(a) a display area<sup>#</sup> not more than 1 m<sup>2</sup>; and</p> <p>(b) a vertical dimension not more than 1 m</p>	
(11)			<p>Erection or alteration of signboard in cylindrical, sculptural, non-planar or free form, which is substantially three-dimensional having –</p> <p>(a) the largest size not more than 600 mm x 600 mm x 600 mm (length x width x height);</p> <p>(b) projection not more than 1 m from the external wall;</p> <p>(c) the works not resulting in additional load to cantilevered slab construction; and</p> <p>(d) the works subject to footnotes (1) and (2)</p>	
(12)			Removal of signboard or	

Type D	Category I	Category II	Category III	Specified Exempted Works
			<p>unauthorized signboard in cylindrical, sculptural, non-planar or other free-form which is substantially three-dimensional, having –</p> <p>(a) the largest size not more than 600 mm x 600 mm x 600 mm (length x width x height); and</p> <p>(b) projection not more than 1 m from the external wall</p>	
(13)	<p>Erection or alteration of free-standing signboard –</p> <p>(a) with a display area<sup>#</sup> not more than 20 m<sup>2</sup>;</p> <p>(b) the highest point of the signboard being at a height of more than 2 m but not more than 6 m from the level of the ground;</p> <p>(c) subject to footnotes (1) to (2); and</p> <p>(d) located at one of the following geographical conditions:-</p> <p>(i) on level ground other than on suspended slab;</p> <p>(ii) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(iii) not less than 5 m from the edge of the crest of a slope</p>		<p>Erection or alteration of free-standing signboard –</p> <p>(a) with a display area<sup>#</sup> not more than 1 m<sup>2</sup> ;</p> <p>(b) the highest point of the signboard being at a height of not more than 2 m above the level of the ground;</p> <p>(c) subject to footnotes (1) to (2); and</p> <p>(d) located at one of the following geographical conditions:-</p> <p>(i) on level ground other than on suspended slab;</p> <p>(ii) at the crest of a slope with a gradient not more than 30 degrees; or</p> <p>(iii) not less than 5 m from the</p>	

Type D	Category I	Category II	Category III	Specified Exempted Works
	having a gradient more than 30 degrees but such slope being not more than 3 m high		edge of the crest of a slope having a gradient more than 30 degrees but such slope being not more than 3 m high	
(14)			Removal of signboard or unauthorized signboard which is free-standing and having –  (a) a display area <sup>#</sup> not more than 20 m <sup>2</sup> ; and  (b) the highest point of the signboard at a height not more than 6 m from the level of the ground	

# “display area” means a planar area on the signboard for display of the advertising message or any other information such as name, registered trade mark or nature of the trade or business in the form of any word, letter, character, figure, symbol, notice or sign printed, painted, carved, engraved or otherwise shown either on plastic or canvas sheet, steel or timber plate, television screen, light emitting diode or plasma screens

Footnote:

- (1) Works not involving any removal, with or without subsequent reinstatement, of approved structural elements except:
  - (a) simply supported beams not of prestressed construction; or
  - (b) simply supported beams not supporting any columns
  
- (2) Works not located within 6 m of Area Number 3 of the Scheduled Areas specified in the Fifth Schedule of the Buildings Ordinance

**(Type E) Structures for Amenities**

<b>Type E</b>	<b>Category I</b>	<b>Category II</b>	<b>Category III</b>	<b>Specified Exempted Works</b>
(1)	Erection or alteration of canopy projecting more than 500 mm but not more than 2 m from the external wall over the main entrance of a building; not involving concrete construction and subject to footnote (1)		Erection or alteration of architectural projection projecting not more than 500 mm from the external wall; not involving concrete construction and subject to footnote (1)	
(2)			<p>Removal of canopy excluding concrete construction, projecting more than 750 mm but not more than 2 m from the external wall</p> <p>Removal of architectural projection, canopy, rack other than drying rack –</p> <p>(a) projecting not more than 750 mm from the external wall; and</p> <p>(b) not involving concrete construction</p>	
(3)	<p>Erection or alteration of metal supporting frame for air-conditioning unit –</p> <p>(a) projecting not more than 600 mm from the external wall;</p> <p>(b) with weight of air-conditioning unit more than 75 kg;</p> <p>(c) with associated provision for disposal of condensate from the unit if applicable; and</p>		<p>Erection or alteration of metal supporting frame for air-conditioning unit –</p> <p>(a) projecting not more than 600 mm from the external wall;</p> <p>(b) with weight of air-conditioning unit not more than 75 kg;</p> <p>(c) with associated provision for disposal of condensate from the unit if applicable; and</p>	

<b>Type E</b>	<b>Category I</b>	<b>Category II</b>	<b>Category III</b>	<b>Specified Exempted Works</b>
	(d) subject to footnote (1)		(d) subject to footnote (1)	
(4)	<p>Erection or alteration of supporting structure for air-conditioning unit or water cooling tower—</p> <p>(a) with weight more than 75 kg;</p> <p>(b) located on suspended slab other than cantilevered slab construction; and</p> <p>(c) no access is provided to the floor of the suspended slab except access for maintenance work</p>		<p>Erection or alteration of supporting structure for air-conditioning unit or water cooling tower –</p> <p>(a) with weight not more than 75 kg;</p> <p>(b) located on suspended slab other than cantilevered slab construction; and</p> <p>(c) no access is provided to the floor of the suspended slab except access for maintenance work</p>	
(5)	<p>Erection or alteration of supporting structure of height not more than 1.5 m for air-conditioning unit or water cooling tower—</p> <p>(a) with weight more than 150 kg; and</p> <p>(b) located on—</p> <p>(i) suspended slab other than cantilevered slab construction, and access to the floor of the suspended slab is provided; or</p> <p>(ii) located on ground</p>		<p>Erection or alteration of supporting structure of height not more than 1.5 m for air-conditioning unit or water cooling tower—</p> <p>(a) with weight not more than 150 kg; and</p> <p>(b) located on—</p> <p>(i) suspended slab other than cantilevered slab construction, and access to the floor of the suspended slab is provided; or</p> <p>(ii) located on ground</p>	
(6)	Removal of supporting structure or unauthorized supporting structure for	Removal of supporting structure or unauthorized supporting structure for		

Type E	Category I	Category II	Category III	Specified Exempted Works
	air-conditioning unit or water cooling tower supported on suspended slab of cantilevered slab construction of span more than 1 m	air-conditioning unit or water cooling tower supported on suspended slab of cantilevered slab construction of span not more than 1 m		
(7)	Removal of supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower with weight more than 1000 kg supported on suspended slab other than cantilevered slab construction	Removal of supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower with weight more than 500 kg but not more than 1000 kg supported on suspended slab other than cantilevered slab construction	Removal of supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower with weight more than 150 kg but not more than 500 kg supported on suspended slab other than cantilevered slab construction  Removal of supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower with weight more than 75 kg but not more than 150 kg supported on suspended slab other than cantilevered slab construction	Removal of supporting structure or unauthorized supporting structure for air-conditioning unit or water cooling tower with weight not more than 75 kg supported on roof or ground
(8)		Removal of supporting frame or unauthorized supporting frame for air-conditioning unit–  (a) projecting more than 750 mm from the external wall; and  (b) not involving concrete construction	Removal of supporting frame or unauthorized supporting frame for air-conditioning unit–  (a) projecting not more than 750 mm from the external wall; and  (b) not involving concrete construction	
(9)			Erection or alteration of drying rack–  (a) projecting not more than 750 mm from the external wall;  (b) at a height of not less than 2.5m above the level of the ground;	

Type E	Category I	Category II	Category III	Specified Exempted Works
			and (c) subject to footnote (1)	
(10)			Removal of drying rack or unauthorized drying rack projecting from the external wall	
(11)	Removal of unauthorized structure affixed to canopy or balcony of cantilevered slab construction of span more than 1 m	Removal of unauthorized structure affixed to canopy or balcony of cantilevered slab construction of span not more than 1 m		
(12)	Removal of unauthorized structure projecting more than 2 m from the external wall	Removal of unauthorized structure projecting more than 750 mm but not more than 2 m from the external wall	Removal of unauthorized structure projecting not more than 750 mm from the external wall	
(13)	Removal of unauthorized structure affixed to canopy or balcony other than cantilevered slab construction of span more than 2 m	Removal of unauthorized structure affixed to canopy or balcony other than cantilevered slab construction of span more than 1 m but not more than 2 m	Removal of unauthorized structure affixed to canopy or balcony other than cantilevered slab construction of span not more than 1 m	

Footnote:

- (1) Works not resulting in additional load to cantilevered slab construction

**(Type F) Repair works**

<b>Type F</b>	<b>Category I</b>	<b>Category II</b>	<b>Category III</b>	<b>Specified Exempted Works</b>
(1)	Repair of structural element and subject to footnote (1)			
(2)		Repair of external rendering or external wall tile with a size of not more than 0.25 m <sup>2</sup> at a height of more than 3 m above the level of the ground		Repair of external rendering or external wall tile with a size of not more than 0.25 m <sup>2</sup> at a height of not more than 3 m above the level of the ground

Footnote:

- (1) Works not resulting in additional load to cantilevered slab construction