

Co-combustion Pilot Plant

Presentation to
Legislative Council Panel on Environmental Affairs
May 23, 2005

Outline

- The Co-combustion Project
- Dioxins
- Other Emissions
- Environmental Impacts
- Monitoring and Control Measures





The Co-combustion Pilot Project

Co-combustion
An Integrated Sustainable Solution!





Hong Kong's Waste - 2004

- Total waste 65,000 tpd
- Sources:
 - C&D material 54,000 tpd
 - MSW 9,500 tpd
 - Special Waste 1,500 tpd
- Disposal:
 - Public Fill 47,000 tpdLand Fill 18,000 tpd





MSW Management Options

- Six technologies under Government review:
 - Anaerobic Digestion
 - Composting
 - Mechanical and Biological Treatment
 - Gasification
 - Incineration
 - Co-combustion

Co-combustion
An Integrated Sustainable Solution!





Waste Management Strategy

- Waste avoidance and minimisation
- Recovery, recycling and reuse
- Bulk reduction and disposal of unrecyclable waste

(Ref: ETWB Legco panel briefing paper February 28, 2005)

Note: The Co-combustion Pilot Plant aims at dealing with the last two of these three legs!





The Co-combustion Project

- Integrated thermal treatment of waste with a Materials Recovery and Recycling Facility ("MRRF")
- Co-combustion is a proprietary patented technology integrating thermal treatment of municipal solid waste with cement manufacture

Co-combustion
An Integrated Sustainable Solution!







Aims of the Pilot Project

- Integrate the waste-to-energy facility with material recovering and recycling
- Achieve a high waste reduction volume
- Reduce dioxin and other air pollutant emissions well below current regulatory levels
- Convert waste to energy to reduce demand for fossil fuel
- Use residue in cement production











Materials Recovery & Recycling

- Sorting
 - Metal
 - Plastics
 - Batteries
- Disposal of recyclables to dealers
- Three protocols to verify the feasibility of different levels of recycling





Products of the Process

- Recyclables
- Energy
- Residue (5% by volume of the MSW)
- Minimal air emissions

Co-combustion
An Integrated Sustainable Solution!





Strengths of the Process

- Dry scrubbing at high temperature gives highly effective removal of dioxin precursors
- Avoids de-novo synthesis by upstream removal of chlorides and control of the critical temperature range
- Residue used in the cement process





The Cement Plant

- Located at Tap Shek Kok since1982
- Manufacturing capacity of 2,000,000 tonnes/annum
- Cement sales to Hong Kong only
- Benefits of Co-combustion to the cement plant:
 - Energy
 - Residue used as a raw material for cement

Co-combustion
An Integrated Sustainable Solution!





Benefits To Community

- Emissions well below world's best practice
- Substantial reduction in landfill needs thus extending the life of the existing landfills
- Sustainable use of land
- An effective MSW recovery and recycling facility
- A competitive cost for the disposal of MSW





Project Programme

- Load commissioning completed in late April 2005
- Operation Production to start in late May/early June 2005 (subject to EPD approval).
- The cumulative operating period is 16 weeks
- Production will cease in late September 2005
- Final reports on emission available at yearend

Co-combustion
An Integrated Sustainable Solution!





Dioxins







Formation of Dioxins

- Dioxins can form when the following are present:
 - Heat
 - Hydrogen
 - Carbon monoxide
 - Chlorine
- Dioxins have existed in nature since man discovered fire









Man-made Sources

- Chemical source. Precursors are:
 - Chlorine
 - Process temperature above 150° C
 - Presence of alkaline conditions

Note: Usually occurs in the liquid phase





Man-made Sources of Dioxins

- Combustion. Precursors are:
 - Chlorine
 - Process temperature between 250°C and 400°C
 - Pollution abatement equipment maintained between 250°C and 400°C

Note: Usually occurs in the gaseous phase

Co-combustion
An Integrated Sustainable Solution!





Man-made Sources of Dioxins

- Secondary
 - Emissions from contaminated sites
 - Atmospheric redistribution of emissions





Dioxin Inventory - Hong Kong

	1997	2007
	(g I-TEQ)	(g I-TEQ)
Power Generation	0.4 - 2.0	0.3 - 1.8
Landfill gas combustion	0.2 - 0.3	0.13 - 0.15
MSW Combustion	21 - 27	0.5
Other industrial sources	0.82 - 3.12	0.64 -1.54
Non-industrial sources	0.11 - 0.66	0.14 - 0.34
Total	23 - 33	2 - 4

- · Assumptions on calculation apply.
- Ref. "An Assessment of Dioxin Emission in Hong Kong" ,March 2000, EPD.

Co-combustion
An Integrated Sustainable Solution!





Eliminating Dioxins

- At source
 - Eliminate the precursors

Note: Difficult without a major shift in consumer attitudes

- In the manufacturing process
 - Breakdown the dioxins
 - Prevent reformation

Note: Demonstrate through the Co-combustion project





Other Air Pollutant Emissions

Co-combustion
An Integrated Sustainable Solution!





Other Air Pollutant Emissions

- Organic Compounds
- Nitrogen Oxides
- Sulphur Dioxide
- Hydrogen Chloride
- Heavy Metals
- Particulates





Eliminating Pollutant Emissions

- Dry scrubbing with calcined lime
- Removal of coarse particles
- Reduction of Nitrogen Dioxide
- Adsorption on activated carbon
- Physical removal of particulates (in a bag house)

Co-combustion
An Integrated Sustainable Solution!





Incineration

- Co-combustion and incineration are both thermal treatment methods but the processes and emissions are different
- The co-combustion process targets a step-change in lowering harmful emissions





Project's Environmental Impacts

Co-combustion
An Integrated Sustainable Solution!





Project Impacts

- Space
 - Minimal impacts site is already in use
- Landscape
 - Minimal impacts site is already in use
- Habitat
 - Minimal impacts site is already in use
- Physical
 - See following abatement measures





Abatement Measures

Air emissions

- Installed equipment controls all emission well below regulatory limits
- Interlocked controls cause automatic shut-down if pre-set limits are exceeded

Traffic

No additional traffic

Co-combustion
An Integrated Sustainable Solution!





Abatement Measures

Water

- Water is used for cooling and is not contaminated by the process
- Water is recycled and no water is discharged to the sea

Noise

- Noise from the plant is not audible across the boundary
- Occupational health limits are not exceeded





Abatement Measures

Waste

- Uncontaminated residue is used for cement production
- Contaminated residue(<1% by volume of incoming waste) is stabilised in concrete, tested for leachates and disposed of at landfills

Odour

- Odour control measures (scented sprays) in place
- Reception hall air changed four times per hour

Co-combustion
An Integrated Sustainable Solution!





Abatement Measures

External Health

- Air emissions well below regulated limits
- Vehicles entering reception hall are washed with disinfectant

Occupational Health

- Medical screening
- Disposable cover-alls, face masks, face screens, gloves
- Decontamination facilities





Monitoring and Control Measures

Co-combustion
An Integrated Sustainable Solution!





Monitoring

- On-site
 - Continuous Emission Monitoring (Information is available live to EPD)
 - Periodic (by an independent monitor)
- Off-site
 - Periodic (by an independent monitor)
- Independent Monitor
 - The Hong Kong Productivity Council using Hong Kong Baptist University





Controls

- Controls allow automatic shut-down if preset limits exceeded
- Regulations impose penalties on company (fines) and its directors (fines and/or custodial sentences)
- EPD is monitoring emission and operational data live
- Emission data is published on GII website





