LEGISLATIVE COUNCIL BRIEF

Import and Export Ordinance (Chapter 60)

IMPORT AND EXPORT (STRATEGIC COMMODITIES) REGULATIONS (AMENDMENT OF SCHEDULE 1) ORDER 2006

INTRODUCTION

The Director-General of Trade and Industry (DGTI) has made the Import and Export (Strategic Commodities) Regulations (Amendment of Schedule 1) Order 2006 ("the Order") to amend Schedule 1 to the Import and Export (Strategic Commodities) Regulations ("the Regulations") in order to reflect the latest changes adopted by various international non-proliferation regimes in their control lists of strategic commodities. The Order is at Annex A.

JUSTIFICATIONS

<u>A</u>

- 2. The Regulations enable Hong Kong to impose licensing controls on the import, export, transshipment, and in some cases, transit of strategic commodities. The licensing system is administered by the Trade and Industry Department (TID) and enforced by the Customs and Excise Department.
- 3. Schedule 1 to the Regulations sets out the strategic commodities which include materials, equipment, software and technology capable of use for both industrial and military purposes. The Schedule has been drawn up on the basis of the control lists adopted by the various international non-proliferation regimes and convention, i.e., the Wassenaar Arrangement (WA), the Australia Group (AG), the Missile Technology Control Regime (MTCR), the Nuclear Suppliers Group (NSG), and the Chemical Weapons Convention (CWC). The Government follows closely the developments in the international scene with regard to the controls over strategic commodities. The Schedule is

under constant review and, where appropriate, is amended to take into account the most up-to-date control lists made by the international regimes and convention. Schedule 1 to the Regulations was last amended in June 2004.

4. Under section 6B of the Import and Export Ordinance, DGTI may, by order published in the Gazette, replace the Schedules to the Regulations or amend them to add or remove an article or class of articles to or from the Schedules to the Regulations.

THE ORDER

- 5. The Order amends Schedule 1 to the Regulations to reflect the revisions adopted by WA, AG and MTCR to their respective control lists up to end-2005. The major changes are set out below.
- (a) the WA (which governs controls over dual-use industrial goods and conventional weapons) has revised its control over a number of items. The changes include removal of control over microprocessors that have multiple data or instruction bus or serial communication ports, certain types of optical weapon sights, a non-fluorinated polymeric substance and some test equipment of semiconductor devices; relaxation of the control thresholds for digital computers from 190,000 million theoretical operations per second (Mtops) to 0.75 Weighted TeraFLOPS and analogue-to-digital converter integrated circuits; and imposition of control on optical detectors that employ silicon focal plane arrays, infrared focal plane arrays based on microbolometer materials, jamming equipment that are designed to interfere with cellular mobile telecommunication services and encryption equipment designed to use quantum cryptography;
- (b) the AG (which maintains controls over chemical and biological weapons agents and precursors as well as their production equipment and technology) has imposed control on additional chemicals that may be used as toxic chemical agents, plant pathogens, and airborne spraying or fogging systems capable of dispersing biological agents in aerosol form; and

(c) the MTCR (which focuses on controls of transfer of missile technology and equipment) has revised its control over a few items. The revisions include clarification of the scope of control on fuel substances used as propellants, and imposition of control on liquid propellant tanks.

LEGISLATIVE TIMETABLE

6. The Order will be gazetted on 4 May 2006 and tabled at the Legislative Council on 10 May 2006.

IMPLICATIONS OF THE PROPOSAL

7. The Order has economic implications as set out at Annex B. The Order is in conformity with the Basic Law, including the provisions concerning human rights. It will not affect the binding effect of the Regulations. It has no financial, civil service, productivity, environmental or sustainability implications.

PUBLIC CONSULTATION

8. The amendments made by the Order are technical in nature. Public consultation is therefore considered not necessary.

PUBLICITY

9. A press release will be issued on the day when the Order is published in the Gazette on 4 May 2006. TID will announce the revised control list through trade circulars, general advisory service and its web portal on the day of gazettal. A spokesman will be available for answering media enquiries.

ENQUIRIES

10. For enquiries on this brief, please contact Mr. Billy Au, Principal Trade Officer of TID, at 2398 5554.

Trade and Industry Department 27 April 2006

IMPORT AND EXPORT (STRATEGIC COMMODITIES) REGULATIONS (AMENDMENT OF SCHEDULE 1) ORDER 2006

ANNEXES

Annex A - The Order

Annex B - Economic Implications

IMPORT AND EXPORT (STRATEGIC COMMODITIES) REGULATIONS (AMENDMENT OF SCHEDULE 1) ORDER 2006

(Made by the Director-General of Trade and Industry under section 6B of the Import and Export Ordinance (Cap. 60))

1. Commencement

Subject to section 6B of the Ordinance, this Order shall come into operation on a day to be appointed by the Director-General of Trade and Industry by notice published in the Gazette.

2. Strategic commodities

Schedule 1 to the Import and Export (Strategic Commodities)
Regulations (Cap. 60 sub. leg. G) is amended -

- (a) by repealing "MUNITIONS LIST";
- (b) by repealing the General Technology Note for the Munitions List;
- (c) by adding -

"MUNITIONS LIST"

before ML1;

- (d) in the Munitions List, in ML1, in the Notes, by adding -
 - "4. ML1(d) does not control optical weapons sights without electronic image processing, with a magnification of 4 times or less, provided they are not specially designed or modified for military use.";

- (e) in the Munitions List, in ML4, in the N.B., by
 repealing "see Note (g)" and substituting "see Note
 7";
- (f) in the Munitions List, in ML6 -
 - (i) in the N.B. where it first appears, by
 repealing "see Note (g)" and substituting "see
 Note 7";
 - (ii) in the English text, by repealing "All wheeldrive vehicles" and substituting "All-wheel
 drive vehicles";
- (g) in the Munitions List, in ML7 -
 - (i) by repealing ""tear gases", radioactive
 materials, related equipment, components,
 materials and "technology"" and substituting
 ""riot control agents", radioactive materials,
 related equipment, components and materials";
 - (ii) by renumbering ML7(b), ML7(c), ML7(d), ML7(e),
 ML7(f), ML7(g), ML7(h) and ML7(i) as ML7(c),
 ML7(d), ML7(e), ML7(f), ML7(g), ML7(h), ML7(i)
 and ML7(j) respectively;
 - (iii) by repealing ML7(a) and substituting -
 - "(a) Biological agents and radioactive

 materials "adapted for use in war" to

 produce casualties in humans or animals,

 degrade equipment or damage crops or the

 environment;";

- (iv) by adding -
 - "(b) Chemical warfare (CW) agents including:
 - (1) CW nerve agents:
 - (a) O-Alkyl (equal to or less than
 C₁₀, including cycloalkyl) alkyl
 (Methyl, Ethyl, n-Propyl or
 Isopropyl) phosphonofluoridates, such as:
 Sarin (GB):O-Isopropyl
 methylphosphonofluoridate (CAS
 107-44-8); and
 Soman (GD):O-Pinacolyl
 methylphosphonofluoridate (CAS
 96-64-0);
 - (b) O-Alkyl (equal to or less than C_{10} , including cycloalkyl)

 N,N-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl)

 phosphoramidocyanidates, such as:
 - Tabun (GA):O-Ethyl
 N,Ndimethylphosphoramidocyanidate
 (CAS 77-81-6);
 - (c) O-Alkyl (H or equal to or less than C_{10} , including cycloalkyl)

S-2-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl)-aminoethyl alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) phosphonothiolates and corresponding alkylated and protonated salts, such as:

VX: O-Ethyl S-2-di-isopropylaminoethyl methyl phosphonothiolate (CAS 50782-69-9);

- (2) CW vesicant agents:
 - (a) Sulphur mustards, such as:
 - (1) 2 Chloroethylchloromethylsul
 phide (CAS 2625-76-5);
 - (2) Bis(2-chloroethyl)
 sulphide (CAS 505-60-2);
 - (3) Bis(2-chloroethylthio)
 methane (CAS 63869-13-6);
 - (4) 1,2-bis (2chloroethylthio) ethane
 (CAS 3563-36-8);
 - (5) 1,3-bis (2chloroethylthio) -npropane (CAS 63905-10-2);

- (7) 1,5-bis (2-chloroethylthio) -n-pentane (CAS 142868-94-8);
- (8) Bis (2chloroethylthiomethyl)
 ether (CAS 63918-90-1);
- (b) Lewisites, such as:
 - chlorovinyldichloroarsine
 (CAS 541-25-3);
 - (2) Tris (2-chlorovinyl)
 arsine (CAS 40334-70-1);
 - (3) Bis (2-chlorovinyl)
 chloroarsine (CAS 4033469-8);
- (c) Nitrogen mustards, such as:
 - (1) HN1: bis (2-chloroethyl)
 ethylamine (CAS 538-07-8);
 - (2) HN2: bis (2-chloroethyl)
 methylamine (CAS 51-75-2);

- (3) HN3: tris (2-chloroethyl) amine (CAS 555-77-1);
- (3) CW incapacitating agents, such as:
 3-Quinuclidinyl benzilate (BZ) (CAS
 6581-06-2);
- (4) CW defoliants, such as:
 - (a) Butyl 2-chloro-4fluorophenoxyacetate (LNF);
 - (b) 2,4,5-trichlorophenoxyacetic
 acid mixed with 2,4 dichlorophenoxyacetic acid
 (Agent Orange);";
- (v) by repealing ML7(d) and substituting -
 - "(d) "Riot control agents", active constituent chemicals and combinations thereof including:
 - (1) α -Bromobenzeneacetonitrile (Bromobenzyl cyanide) (CA) (CAS 5798-79-8);
 - (2) [(2-chlorophenyl) methylene]
 propanedinitrile (o Chlorobenzylidenemalononitrile) (CS)
 (CAS 2698-41-1);

27-4);

- (4) Dibenz-(b,f)-1,4-oxazephine (CR) (CAS 257-07-8);
- (6) N-Nonanoylmorpholine (MPA) (CAS
 5299-64-9);

Notes:

- 1. ML7(d) does not control "riot control agents" individually packaged for personal self defence purposes.
- 2. ML7(d) does not control active constituent chemicals, and combinations thereof identified and packaged for food production or medical purposes.";

(vi) in ML7(e) -

- (A) by repealing "or ML7(c)" and substituting
 ", ML7(b) or ML7(d)";
- (B) by repealing "ML7(b)" and substituting
 "ML7(c)";

(vii) in ML7(f) -

(A) in ML7(f)(1), by repealing "or ML7(c)"
and substituting ", ML7(b) or ML7(d)";

- (B) in ML7(f)(2) and (3), by repealing
 "ML7(a)" and substituting "ML7(a) or
 ML7(b)";
- (C) in the Note, by repealing "ML7(e)(1)" and substituting "ML7(f)(1)";

(viii) in ML7(g) -

- (A) by repealing "or ML7(c)" and substituting
 ", ML7(b) or ML7(d)";
- (B) in the Note, by repealing "ML7(f)" and substituting "ML7(g)";
- (ix) in ML7(h), by repealing "ML7(a)" and
 substituting "ML7(b)";
 - (x) in ML7(i) -
 - (A) by repealing "ML7(a)" and substituting
 "ML7(b)";
 - (B) by repealing "ML7(h)(1)" and substituting "ML7(i)(1)";
- (xi) by repealing ML7(j);
- (xii) in Note 1 -
 - (A) by repealing "and ML7(c)" and
 substituting ", ML7(b) and ML7(d)";
 - (B) by repealing Note 1(f);
- (xiii) in Note 2 -
 - (A) by repealing ""technology"," where it
 twice appears;

- (B) by repealing "ML7(g), ML7(h)(2) and ML7(i)(3)" and substituting "ML7(h) and ML7(i)(2)";
- (h) in the Munitions List, in ML8 -
 - (i) in ML8(d)(3), by repealing the Note and substituting -

"Notes:

- 1. ML8(d)(3) does not control Chlorine
 Trifluoride.
- 2. ML8(d)(3) does not control Nitrogen
 Trifluoride in its gaseous state.";
- (ii) in ML8(f)(4)(d), by repealing "(CAS 319904-297)" and substituting "(CAS 31904-29-7)";
- (i) in the Munitions List, in ML9, in the N.B., by repealing "see Note (g)" and substituting "see Note 7";
- (j) in the Munitions List, in ML10 -
 - (i) by adding ""lighter-than-air vehicles"," after
 ""Aircraft",";
 - (ii) in the N.B., by repealing "see Note (g)" and
 substituting "see Note 7";
 - (iii) in ML10(a), in the Chinese text, by repealing "部件" and substituting "零件";
 - (iv) in ML10(b) -
 - (A) by adding "and "lighter-than-air
 vehicles"" after "Other "aircraft"";

- (B) in the Chinese text, by repealing "部件" and substituting "零件";
- (v) in ML10(c) -
 - (A) in the Chinese text, by repealing "部件" and substituting "零件";
 - (B) in ML10(c)(1), by repealing "and autonomous programmable vehicles" and substituting ", autonomous programmable vehicles and "lighter-than-air vehicles";
- (vi) in ML10(d), in the Chinese text, by repealing
 "部件" and substituting "零件";
- (vii) in ML10(e), in the Chinese text, by repealing
 "部件" and substituting "零件";
- (viii) in ML10(h), by adding ", and specially
 designed components therefor" after "as
 follows";
- (k) in the Munitions List, by repealing ML11 and substituting -
 - "ML11 Electronic equipment, not controlled elsewhere in the Munitions List, as follows, and specially designed components therefor:
 - (a) Electronic equipment specially
 designed for military use;

Note:

ML11(a) includes:

- 1. Electronic countermeasure and
 electronic counter countermeasure equipment (i.e.,
 equipment designed to introduce
 extraneous or erroneous signals
 into radar or radio
 communication receivers or
 otherwise hinder the reception,
 operation or effectiveness of
 adversary electronic receivers
 including their countermeasure
 equipment), including jamming
 and counter-jamming equipment;
- Frequency agile tubes;
- 3. Electronic systems or equipment designed either for surveillance and monitoring of the electro-magnetic spectrum for military intelligence or security purposes, or for counteracting such surveillance and monitoring;

- 4. Underwater countermeasures,

 including acoustic and magnetic

 jamming and decoy equipment

 designed to introduce

 extraneous or erroneous signals

 into sonar receivers;
- 5. Data processing security
 equipment, data security
 equipment and transmission and
 signalling line security
 equipment, using ciphering
 processes;
- 6. Identification, authentification and keyloader equipment and key management, manufacturing and distribution equipment;
- Guidance and navigation equipment.
- (1) in the Munitions List, in ML12, by repealing Note
 3;
- (m) in the Munitions List, in ML17 -
 - (i) in ML17(m), by repealing "and" at the end;
 - (ii) in ML17(n), by adding "and" at the end;

- (iii) by adding -
 - "(o) Laser protection equipment (e.g., eye and sensor protection) specially designed for military use;";
- (n) in the Munitions List, in ML18 -
 - (i) in Note 2(b)(2), by repealing "Note 3" and substituting "Note 1";
 - (ii) in Note 2(b)(3), by repealing "see ML7(f)" and substituting "see ML7(g)";
- (o) in the Munitions List, in ML21(b)(3), by repealing
 "ML7(f)" and substituting "ML7(g)";
- (p) in the Munitions List, by repealing ML22 and substituting -

"ML22 "Technology" as follows:

- (a) "Technology", other than that
 specified in ML22(b), which is
 "required" for the "development",
 "production" or "use" of items
 controlled in the Munitions List;
- (b) "Technology" as follows:
 - (1) "Technology" "required" for the design of, the assembly of components into, and the operation, maintenance and repair of complete production installations for items

- controlled in the Munitions

 List, even if the components of such production installations

 are not controlled;
- "Technology" "required" for the
 "development" and "production"
 of small arms even if used to
 produce reproductions of
 antique small arms;
- "Technology" "required" for the
 "development", "production" or
 "use" of toxicological agents,
 related equipment or components
 controlled by ML7(a) to ML7(g);
- "Technology" "required" for the
 "development", "production" or
 "use" of "biopolymers" or
 cultures of specific cells
 controlled by ML7(h);
- (5) "Technology" "required"
 exclusively for the
 incorporation of "biocatalysts",
 controlled by ML7(i)(1), into
 military carrier substances or
 military material;

Notes:

- 1. "Technology" "required" for the
 "development", "production" or
 "use" of items controlled in
 the Munitions List remains
 under control even when
 applicable to any uncontrolled
 item.
- - (a) Which is the minimum
 necessary for the
 installation, operation,
 maintenance (checking) and
 repair of those items
 which are not controlled
 or whose export has been
 authorized;
 - (b) Which is "in the public
 domain", "basic scientific
 research" or the minimum
 necessary information for
 patent applications;
 - (c) For magnetic induction for
 continuous propulsion of
 civil transport devices.";

- (q) in the Dual-use Goods List, in Category 1, in subcategory 1A -
 - (i) in 1A102, by repealing "specified in" where it twice appears and substituting "controlled by";
 - (ii) in 1A202, by repealing "specified in" wherever
 it appears and substituting "controlled by";
- (r) in the Dual-use Goods List, in Category 1, in subcategory 1B -
 - (i) in 1B102, by repealing "specified in" wherever it appears and substituting "controlled by";
 - (ii) in 1B115, by repealing "specified in" wherever
 it appears and substituting "controlled by";
 - - (iv) in 1B201, by repealing "specified in" wherever
 it appears and substituting "controlled by";
 - (v) in 1B229(b), by repealing "specified in" and substituting "controlled by";
- (s) in the Dual-use Goods List, in Category 1, in subcategory 1C -
 - (i) in 1C001(c) -
 - (A) by repealing "bulk electrical
 conductivity" and substituting "'bulk
 electrical conductivity'";
 - (B) by repealing "sheet (surface)
 resistivity" where it first appears and

- substituting "'sheet (surface)
 resistivity'";
- (C) in the Technical Note, by repealing "Bulk
 electrical conductivity and sheet
 (surface) resistivity" and substituting
 "'Bulk electrical conductivity' and
 'sheet (surface) resistivity'";

(ii) in 1C008 -

- (A) in 1C008(a)(4), by repealing "determined using the dry method described in ASTM D-3418";
- (B) in 1C008(b), by repealing "ASTM D-648,
 method A," and substituting "ISO 75-3
 (2004),";
- (C) by repealing 1C008(c)(1);
- (D) in 1C008(f), by adding "having a glass transition temperature (T_g) exceeding 513 K (240°C)" after "Polybiphenylenethersulphone";
- (E) in the Technical Note, by repealing "ASTM D-3418 using the dry method" and substituting "ISO 11357-2 (1999) or national equivalents";

(iii) in 1C101 -

(A) by repealing ""missiles"" and
substituting "'missiles'";

- (B) by adding at the end "Technical Note:
 - In 1C101, 'missiles' means complete rocket systems and "unmanned aerial vehicle" systems capable of a range exceeding 300 km.";
- (iv) in 1C102, by repealing "specified in" where it
 twice appears and substituting "controlled by";
 - (v) in 1C107 -
 - (A) by repealing "specified in" and substituting "controlled by";
 - (B) by repealing 1C107(a) and substituting -
 - "(a) Fine grain graphites with a bulk density of at least 1.72 g/cc measured at 15°C and having a grain size of 100 x 10⁻⁶ m (100 µm) or less, usable for rocket nozzles and reentry vehicle nose tips, which can be machined to any of the following products:
 - (1) Cylinders having a diameter of 120 mm or greater and a length of 50 mm or greater;
 - (2) Tubes having an inner diameter of 65 mm or greater and a wall thickness of 25 mm or greater

and a length of 50 mm or greater; or

(3) Blocks having a size of 120 mm
x 120 mm x 50 mm or greater;

N.B.:

See also 0C004.";

- (C) in 1C107(c), by repealing "at frequencies
 from 100 Hz to 10 000 MHz" and
 substituting "at any frequency from 100
 MHz to 100 GHz";
- (vi) in 1C111 -
 - (A) in 1C111(a), by adding -
 - "(4) Hydrazine derivatives, other than those controlled by the Munitions

 List, usable as rocket fuel substances;";
 - (B) in 1C111(c)(1), by repealing "Butacene"
 and substituting "carboranes, decaboranes,
 pentaboranes and derivatives thereof";
 - (C) by repealing 1C111(c)(6) and substituting -
 - "(6) Ferrocene derivatives as follows:
 - (a) See the Munitions List for catocene;

- (b) Ethyl ferrocene;
- (c) Propyl ferrocene;
- (d) See the Munitions List for nbutyl ferrocene;
- (e) Pentyl ferrocene;
- (f) Dicyclopentyl ferrocene;
- (g) Dicyclohexyl ferrocene;
- (h) Diethyl ferrocene;
- (i) Dipropyl ferrocene;
- (j) Dibutyl ferrocene;
- (k) Dihexyl ferrocene;
- (1) Acetyl ferrocenes;
- (m) See the Munitions List for
 ferrocene carboxylic acids;
- (n) See the Munitions List for butacene;
- (o) Other ferrocene derivatives
 usable as rocket propellant
 burning rate modifiers, other
 than those controlled by the
 Munitions List;";
- (vii) in 1C116, by repealing "of 1 500 MPa or greater" and substituting "equal to or greater

than 1.5 GPa";

- - (ix) in 1C210, by repealing "specified in" where it twice appears and substituting "controlled by";
 - (x) in 1C216, by repealing "specified in" and substituting "controlled by";
 - (xi) in 1C240, by repealing "specified in" where it twice appears and substituting "controlled by";
 - (xii) in 1C350 -
 - (A) in 1C350(29), in the English text, by
 repealing "o-Ethyl-2diisopropylaminoethyl" and substituting
 "o-Ethyl-2-di-isopropylaminoethyl";
 - (B) by adding -
 - "(55) Methyl phosphonic acid (993-13-5);
 - (56) Diethyl methylphosphonate (683-08-9);
 - (57) N, N-Dimethyl aminophosphoryl dichloride (677-43-0);
 - (58) Triisopropyl phosphite (116-17-6);
 - (59) Ethyl diethanolamine (139-87-7);
 - (60) O,O-Diethyl phosphorothioate (2465-65-8);
 - (61) O,O-Diethyl phosphorodithioate (298-06-6);

- (62) Sodium hexafluorosilicate (16893-859);
- (63) Methyl phosphonothioic dichloride
 (676-98-2);";
- (xiii) in 1C351, by repealing -

"except:

Any goods controlled by 1C351 in the form of a "vaccine" or "immunotoxin"."

and substituting -

"Note:

1C351 does not control "vaccines" or
"immunotoxins".";

(xiv) in 1C352, by repealing -

"except:

Any goods controlled by 1C352 in the form of a "vaccine"."

and substituting -

"Note:

1C352 does not control "vaccines".";

"Technical Notes:

 Genetic elements include, inter alia, chromosomes, genomes, plasmids, transposons and vectors whether genetically modified or unmodified.

- 2. Nucleic acid sequences associated with the pathogenicity of any of the "microorganisms" controlled by 1C351(a) to (c) or 1C352 or 1C354 mean any sequence specific to the relevant listed "microorganism":
 - that in itself or through its transcribed or translated products represents a significant hazard to human, animal or plant health; or
 - that is known to enhance the ability of a "microorganism" controlled by 1C351(a) to (c) or 1C352 or 1C354, or any other organism into which it may be inserted or otherwise integrated, to cause serious harm to human, animal or plant health.
- 3. 1C353 does not apply to nucleic acid sequences associated with the pathogenicity of enterohaemorrhagic

 Escherichia coli, serotype 0157 and other verotoxin producing strains, other than those coding for the verotoxin, or for its sub-units.";

(xvi) in 1C354 -

- (A) by renumbering 1C354(a) and 1C354(b) as 1C354(b) and 1C354(c) respectively;
- (B) by adding -
 - "(a) Viruses, whether natural, enhanced or modified, either in the form of "isolated live cultures" or as material (including living material) which has been deliberately inoculated or contaminated with such cultures, as follows:
 - (1) Potato Andean latent tymovirus;
 - (2) Potato spindle tuber viroid;";
- (C) in 1C354(b), by adding -
 - "(3) Xanthomonas oryae pv. oryzae (Pseudomonas campestris pv. oryzae);
 - (4) Clavibacter michiganensis subsp.

 Sepedonicus (Corynebacterium michiganensis subsp. Sepedonicum or Corynebacterium Sepedonicum);
 - (Pseudomonas solanacearum Races 2 and 3 and 3 or Burkholderia solanacearum Races 2 and 3);";

- (t) in the Dual-use Goods List, in Category 1, in subcategory 1D, in 1D101, by repealing "specified in" and substituting "controlled by";
- (u) in the Dual-use Goods List, in Category 2, in subcategory 2B -
 - (i) by repealing Technical Note 2 to this subcategory and substituting -
 - "2. For the purposes of 2B, the number of axes which can be coordinated simultaneously for "contouring control" is the number of axes along or around which, during processing of a workpiece, simultaneous and interrelated motions are performed between the workpiece and a tool. This does not include any additional axes along or around which other relative motions within the machine are performed, such as:
 - (a) Wheel-dressing systems in grinding
 machines;
 - (b) Parallel rotary axes designed for
 mounting of separate workpieces;

- (c) Co-linear rotary axes designed for manipulating the same workpiece by holding it in a chuck from different ends.";
- (ii) in 2B001(c), by repealing Note 2 and substituting -
 - "2. Machines designed specifically as jig grinders that do not have a z-axis or a w-axis, with a positioning accuracy with "all compensations available" less (better) than 3 μm according to ISO 230/2 (1997) or national equivalents.";
- (iii) in 2B002, by repealing "Numerically controlled
 machine tools using a magnetorheological
 finishing (MRF) process;" and substituting "Numerically controlled machine tools using a
 magnetorheological finishing (MRF) process
 equipped to produce non-spherical surfaces and
 having any of the following characteristics:
 - (a) Finishing the form to less (better) than $1.0 \ \mu m; \ or$
 - (b) Finishing to a roughness less (better)
 than 100 nm rms;";
 - (iv) in 2B005 -
 - (A) in 2B005(a), by repealing ""Stored programme controlled" chemical" and

- substituting "Chemical";
- (B) in 2B005(b), by repealing ""Stored
 programme controlled" ion" and
 substituting "Ion";
- (C) in 2B005(c), by repealing ""Stored
 programme controlled" electron" and
 substituting "Electron";
- (D) in 2B005(d), by repealing ""Stored
 programme controlled" plasma" and
 substituting "Plasma";
- (E) in 2B005(e), by repealing ""Stored
 programme controlled" sputter" and
 substituting "Sputter";
- (F) in 2B005(f), by repealing ""Stored
 programme controlled" cathodic" and
 substituting "Cathodic";
- (G) in 2B005(g), by repealing ""Stored
 programme controlled" ion" and
 substituting "Ion";
- (v) in 2B006 -
 - (A) by repealing "and equipment, as follows"
 and substituting ", equipment and
 "electronic assemblies", as follows";
 - (B) in 2B006(a), by repealing ", "numerically controlled" or "stored programme controlled"" and substituting "or

- "numerically controlled"";
- (C) in 2B006(b)(1), by adding before the Note -
 - "(d) "Electronic assemblies" specially designed to provide feedback capability in systems controlled by 2B006(b)(1)(c);";
- (D) in the Note, by repealing "without closed
 or open loop feedback" and substituting
 "with an automatic control system that is
 designed to use no feedback techniques";
- (vi) in 2B104 -
 - (A) by repealing "specified in" and substituting "controlled by";
 - (B) in 2B104(a), by repealing "of 69 MPa or greater" and substituting "equal to or greater than 69 MPa";
- (viii) in 2B109, by repealing "specified in" wherever it appears and substituting "controlled by";
 - (ix) in 2B116 -

- (A) in 2B116(a), by repealing "at 10 g rms or more over the entire range 20 Hz to 2 000 Hz and imparting forces of 50 kN, measured 'bare table', or greater" and substituting "at an acceleration equal to or greater than 10 g rms between 20 Hz to 2 kHz and imparting forces equal to or greater than 50 kN, measured 'bare table'";
- (B) in 2B116(c), by repealing "of 50 kN,
 measured 'bare table', or greater" and
 substituting "equal to or greater than
 50 kN, measured 'bare table'";
- (C) in 2B116(d), by repealing "of 50 kN,
 measured 'bare table', or greater" and
 substituting "equal to or greater than
 50 kN, measured 'bare table'";
- (x) in 2B117, by repealing "specified in" and substituting "controlled by";
- (xi) in 2B119(b), by repealing "specified in" and substituting "controlled by";

- (xiii) in Note (b) to 2B201(a), by repealing 0.03 mm and substituting $30 \text{ } \mu\text{m}$;
 - (xiv) in 2B204, by repealing "specified in" where it
 twice appears and substituting "controlled by";
 - (xv) in 2B206, by repealing "those specified in"
 and substituting "those controlled by";
 - (xvi) in 2B207, by repealing "specified in" where it
 twice appears and substituting "controlled by";
- (xvii) in 2B209, by repealing "specified in" and substituting "controlled by";
- (xviii) in 2B226(b), by repealing "specified in" and substituting "controlled by";
 - (xix) in 2B227(c), by repealing "specified in" and substituting "controlled by";
 - (xx) in 2B350 -
 - (A) in 2B350(b), by repealing "specified in"
 and substituting "controlled by";
 - (B) in 2B350(i), by repealing ", canned
 drive, magnetic drive, bellows or
 diaphragm pumps," and substituting "and
 seal-less pumps";
 - (xxi) in 2B351(a), by repealing "specified in" and substituting "controlled by";
 - (xxii) in 2B352, by repealing 2B352(d) and substituting -

- "(d) Cross (tangential) flow filtration equipment and component as follows:
 - (1) Cross (tangential) flow filtration equipment capable of separation of pathogenic "microorganisms", viruses, "toxins" or cell cultures, without the propagation of aerosols, and having both of the following characteristics:
 - (a) A total filtration area equal to or greater than 1 m^2 ; and
 - (b) Capable of being 'sterilised'
 or 'disinfected' in-situ;

 Technical Note:

In 2B352(d)(1)(b), 'sterilised' denotes the elimination of all viable microbes from the equipment through the use of either physical (e.g. steam) or chemical agents. 'Disinfected' denotes the destruction of potential microbial infectivity in the equipment through the use of chemical agents with a germicidal effect. Disinfection and sterilisation are distinct

from sanitization, the latter referring to cleaning procedures designed to lower the microbial content of equipment without necessarily achieving elimination of all microbial infectivity or viability.

(2) Cross (tangential) flow filtration components (e.g. modules, elements, cassettes, cartridges, units or plates) with filtration area equal to or greater than 0.2 m² for each component and designed for use in cross (tangential) flow filtration equipment controlled by 2B352(d);

Note:

2B352(d) does not control reverse osmosis equipment, as specified by the manufacturer.";

- (v) in the Dual-use Goods List, in Category 2, in subcategory 2D, in 2D101, by repealing "specified in" and substituting "controlled by";
- (w) in the Dual-use Goods List, in Category 2, in subcategory 2E, in 2E101, by repealing "specified in" and substituting "controlled by";

- (x) in the Dual-use Goods List, in Category 3, in subcategory 3A -
 - (i) in 3A001 -
 - (A) by repealing 3A001(a)(3) and substituting -
 - "(3) "Microprocessor microcircuits",

 "microcomputer microcircuits" and

 microcontroller microcircuits,

 manufactured from a compound

 semiconductor and operating at a

 clock frequency exceeding 40 MHz;

 Note:
 - 3A001(a)(3) includes digital signal processors, digital array processors and digital coprocessors.";
 - (B) by repealing 3A001(a)(5)(a) and substituting -
 - "(a) Analogue-to-digital converters having any of the following:
 - (1) A resolution of 8 bit or more, but less than 10 bit, with an output rate greater than 500 million words per second;
 - (2) A resolution of 10 bit or more, but less than 12 bit, with an output rate greater than 200

- million words per second;
- (3) A resolution of 12 bit with an
 output rate greater than 50
 million words per second;
- (4) A resolution of more than 12
 bit but equal to or less than
 14 bit with an output rate
 greater than 5 million words
 per second; or
- (5) A resolution of more than 14
 bit with an output rate greater
 than 1 million words per
 second;";
- (C) in 3A001(a)(5), by repealing the

 Technical Notes and substituting
 "Technical Notes:
 - 1. A resolution of n bit corresponds to a quantisation of 2^n levels.
 - 2. The number of bits in the output word is equal to the resolution of the analogue-to-digital converter.
 - 3. The output rate is the maximum output rate of the converter, regardless of architecture or oversampling. Vendors may also refer to the output rate as sampling rate,

conversion rate or throughput rate.

It is often specified in megahertz

(MHz) or mega samples per second

(MSPS).

- 4. For the purpose of measuring output rate, one output word per second is equivalent to one Hertz or one sample per second.";
- (D) in 3A001(b)(2), by repealing Note 2 and substituting -
 - "2. The control status of the MMIC whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by 3A001(b)(2)(a) to 3A001(b)(2)(f), is determined by the lowest average output power control threshold.";
- (E) in 3A001(b)(3), by repealing "Microwave"
 and substituting "Discrete microwave";
- (F) in 3A001(b)(3), by repealing the Note and substituting -

"Note:

The control status of a transistor whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by

- 3A001(b)(3)(a) to 3A001(b)(3)(e), is determined by the lowest average output power control threshold.";
- (G) in 3A001(b)(4)(f), by adding at the end "Technical Note:
 - 3.2 GHz should be used as the lowest operating frequency (f_{GHz}) in the formula in 3A001(b)(4)(f)(3), for amplifiers that have a rated operation range extending downward to 3.2 GHz and below $[d\le15cm*GHz/3.2 GHz].";$
- (H) in 3A001(b)(4), by repealing Note 2 and substituting -
 - "2. The control status of an item whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by 3A001(b)(4)(a) to 3A001(b)(4)(e), is determined by the lowest average output power control threshold.";
- (ii) by repealing 3A002(c) and substituting -
 - "(c) Radio frequency "signal analysers", as follows:

- (1) "Signal analysers" capable of analysing any frequencies exceeding 31.8 GHz but not exceeding 37.5 GHz and having a 3 dB resolution bandwidth (RBW) exceeding 10 MHz;
- (2) "Signal analysers" capable of
 analysing frequencies exceeding 43.5
 GHz;
- "real-time bandwidth" exceeding 500
 kHz;

Note:

3A002(c)(3) does not control those "dynamic signal analysers" using only constant percentage bandwidth filters (also known as octave or fractional octave filters).";

- - (iv) in 3A225, by repealing "specified in" and
 substituting "controlled by";
 - (v) in 3A226, by repealing "specified in" and substituting "controlled by";
 - (vi) in 3A227, by repealing "specified in" and substituting "controlled by";

- (y) in the Dual-use Goods List, in Category 3, in subcategory 3B -
 - (i) by repealing 3B001(a)(1) and substituting -
 - "(1) Equipment capable of producing a layer of any material other than silicon with a thickness uniform to less than ± 2.5% across a distance of 75 mm or more;";
 - (ii) in 3B001(c)(1)(a), by repealing "0.3 μ m" and substituting "180 nm";
 - (iii) in 3B001(c)(2)(a), by repealing "0.3 μ m" and substituting "180 nm";
 - (iv) in 3B001(f)(1)(a), by repealing "350" and substituting "245";
 - (v) in 3B001(f)(1)(b) -
 - (A) by repealing "0.35 μ m" and substituting "180 nm";
 - (B) in the Technical Note, by repealing "μm" and substituting "nm";
 - (C) in the Technical Note, by repealing "0.7" and substituting "0.45";
 - (vi) in 3B002 -

 - (B) by repealing 3B002(b);

- (z) in the Dual-use Goods List, in Category 4, in subcategory 4A -
 - (i) by repealing 4A003(b) and substituting -
 - "(b) "Digital computers" having an "Adjusted

 Peak Performance" ("APP") exceeding 0.75

 Weighted TeraFLOPS (WT);";
 - (ii) in 4A003(c) -
 - (A) by repealing ""computing elements"
 ("CEs") so that the "CTP"" and
 substituting "processors so that the
 "APP"";
 - (B) in Note 1, by repealing "4A003(d) or";
 - (iii) in 4A101, by adding ", "unmanned aerial
 vehicles" controlled by 9A012" after "9A004";
 - (iv) in 4A102, by adding ", "unmanned aerial
 vehicles" controlled by 9A012" after "9A004";
- (za) in the Dual-use Goods List, in Category 4, in subcategory 4D -
 - (i) in 4D001(b)(1), by repealing "a "composite
 theoretical performance" ("CTP") exceeding
 28 000 Mtops" and substituting "an "Adjusted
 Peak Performance" ("APP") exceeding 0.04
 Weighted TeraFLOPS (WT)";
 - (ii) in 4D001(b)(2), by repealing ""computing
 elements" ("CEs") so that the "CTP"" and
 substituting "processors so that the "APP"";

- (zb) in the Dual-use Goods List, in Category 4, in subcategory 4E -
 - (i) in 4E001(b)(1), by repealing "a "composite
 theoretical performance" ("CTP") exceeding
 28 000 Mtops" and substituting "an "Adjusted
 Peak Performance" ("APP") exceeding 0.04
 Weighted TeraFLOPS (WT)";
 - (ii) in 4E001(b)(2), by repealing ""computing
 elements" ("CEs") so that the "CTP"" and
 substituting "processors so that the "APP"";
 - (iii) by adding at the end -

"TECHNICAL NOTE ON "ADJUSTED PEAK PERFORMANCE" ("APP")

"APP" is an adjusted peak rate at which
"digital computers" perform 64-bit or larger
floating point additions and multiplications.

Abbreviations used in this Technical Note:

- n number of processors in the "digital computer"
- i processor number (i,...n)
- t_i processor cycle time ($t_i = 1/F_i$)
- F_i processor frequency
- R, peak floating point calculating rate
- W_i architecture adjustment factor

"APP" is expressed in Weighted TeraFLOPS (WT), in units of 10^{12} adjusted floating point operations per second.

Outline of the "APP" calculation method:

1. For each processor i, determine the peak number of 64-bit or larger floating point operations, FPO_i, performed per cycle for each processor in the "digital computer".

Note: In determining FPO, include only 64-bit or larger floating point additions or multiplications or both.

All floating point operations must be expressed in operations per processor cycle; operations requiring multiple cycles may be expressed in fractional results per cycle. For processors not capable of performing calculations on floating point operands of 64-bits or more, the effective calculating rate R is zero.

- 2. Calculate the floating point rate R for each processor $R_i \, = \, FPO_i/t_i$
- 3. Calculate "APP" $\text{"APP"} = W_1 \times R_1 + W_2 \times R_2 + \ldots + W_n \times R_n$
- 4. For 'vector processors', $W_i = 0.9$. For non-'vector processors', $W_i = 0.3$.

Notes:

- 1. For processors that perform compound operations in a cycle, such as addition and multiplication, each operation is counted.
- 2. For a pipelined processor, the effective calculating rate R is the faster of the pipelined rate, once the pipeline is full, or the non-pipelined rate.
- 3. The calculating rate R of each contributing processor is to be calculated at its maximum value theoretically possible before the

"APP" of the combination is derived.

Simultaneous operations are assumed to exist when the computer manufacturer claims concurrent, parallel, or simultaneous operation or execution in a manual or brochure for the computer.

- 4. Do not include processors that are limited to input/output and peripheral functions (e.g., disk drive, communication and video display) when calculating "APP".
- 5. "APP" values are not to be calculated for processor combinations interconnected by "Local Area Networks", Wide Area Networks, Input/Output shared connections/devices, Input/Output controllers and any communication interconnection implemented by "software".

- 1) processor combinations containing processors specially designed to enhance performance by aggregation, operating simultaneously and sharing memory; or 2) multiple memory/processor combinations operating simultaneously utilizing specially designed hardware.
- 7. A 'vector processor' is defined as a processor with built-in instructions that perform multiple calculations on floating-point vectors (one-dimensional arrays of 64-bit or larger numbers) simultaneously, and having at least 2 vector functional units and at least 8 vector registers of at least 64 elements each.";
- (zc) in the Dual-use Goods List, in Category 5, in subcategory 5A1 -
 - (i) in 5A001 -
 - (A) in 5A001(b)(3), by adding "not controlled by 5A001(b)(4), and" before "having any";

- (B) by repealing 5A001(b)(4) and substituting -
 - "(4) Being radio equipment employing

 ultra-wideband modulation techniques,

 having user programmable

 channelizing codes, scrambling codes

 or network identification codes, and

 having any of the following

 characteristics:
 - (a) A bandwidth exceeding 500 MHz;
 - (b) A "fractional bandwidth" of 20%
 or more.";
- (C) in 5A001(b)(6) -
 - (I) by repealing "provide voice coding"
 and substituting "provide 'voice
 coding'";
 - (II) by repealing the Technical Note and substituting -

"Technical Notes:

1. For variable rate 'voice
 coding', 5A001(b)(6) applies to
 the voice coding output of
 continuous speech.

- 2. For the purpose of 5A001(b)(6), 'voice coding' is defined as the technique to take samples of human voice and then convert these samples into a digital signal, taking into account specific characteristics of human speech.";
- (D) in 5A001(d), by repealing "31" and substituting "31.8";
- (E) by adding -
 - "(e) Radio direction finding equipment operating at frequencies above 30

 MHz and having all of the following characteristics, and specially designed components therefor:
 - (1) "Instantaneous bandwidth" of 10

 MHz or more; and
 - (2) Capable of finding a line of bearing (LOB) to non-cooperating radio transmitters with a signal duration of less than 1 ms;
 - (f) Jamming equipment specially designed or modified to intentionally and selectively interfere with, deny,

inhibit, degrade or seduce cellular mobile telecommunications services, and having any of the following characteristics, and specially designed components therefor:

- (1) Simulating the functions of Radio Access Network (RAN) equipment; or
- (2) Detecting and exploiting
 specific characteristics of the
 mobile telecommunications
 protocol employed (e.g., GSM);

N.B.:

For GNSS jamming equipment, see the Munitions List.";

Technical Note:

In 5A101, 'missiles' means complete rocket systems and "unmanned aerial vehicle" systems capable of a range exceeding 300 km.

Note:

5A101 does not control:

- (a) Equipment designed or modified
 for manned aircraft or
 satellites;
- (b) Ground based equipment designed or modified for terrestrial or marine applications;
- (c) Equipment designed for
 commercial, civil or safety of
 life (e.g. data integrity,
 flight safety) GNSS services.";
- (zd) in the Dual-use Goods List, in Category 5, in subcategory 5D1 -
 - (i) by repealing 5D001(c) and substituting -
 - "(c) Specific "software" specially designed or
 modified to provide characteristics,
 functions or features of equipment
 controlled by 5A001 or 5B001;";
 - (ii) in 5D101, by repealing "specified in" and substituting "controlled by";
- (ze) in the Dual-use Goods List, in Category 5, in subcategory 5A2 -
 - (i) in 5A002(a)(5), by adding "not controlled by 5A002(a)(6)" after ""spread spectrum" systems";

- (ii) by repealing 5A002(a)(6) and substituting -
 - "(6) Designed or modified to use cryptographic techniques to generate channelizing codes, scrambling codes or network identification codes, for systems using ultra-wideband modulation techniques, and having any of the following characteristics:
 - (a) A bandwidth exceeding 500 MHz; or
 - (b) A "fractional bandwidth" of 20% or
 more;";
- (iii) in 5A002(a), by adding -
 - "(9) Designed or modified to use "quantum cryptography";

Technical Note:

"Quantum cryptography" is also known as quantum key distribution (QKD).";

- (iv) in 5A002(a) -
 - (A) in Note (c)(2)(b), by repealing "or";
 - (B) in Note (c)(3), by adding "or" at the end;
 - (c) in Note (c), by adding -
 - "(4) Encryption or decryption or both for protection of libraries, design attributes, or associated data for the design of semiconductor devices

or integrated circuits;";

- (zf) in the Dual-use Goods List, in Category 6, in subcategory 6A -
 - (i) in 6A001(a)(2)(a), in the Note, by repealing
 everything after "of the other equipment." and
 substituting -
 - "(1) Incorporating continuous flexible sensing elements;
 - (2) Incorporating flexible assemblies of discrete sensing elements with either a diameter or length less than 20 mm and with a separation between elements of less than 20 mm;
 - (3) Having any of the following sensing elements:
 - (a) Optical fibres;
 - (b) 'Piezoelectric polymer films' other
 than polyvinylidene fluoride (PVDF)
 and its copolymers {P(VDF-TrFE) and
 P(VDF-TFE)}; or
 - (c) 'Flexible piezoelectric composites';
 - (4) A hydrophone sensitivity better than -180 dB at any depth with no acceleration compensation;

- (5) When designed to operate at depths exceeding 35 m with acceleration compensation; or
- (6) Designed for operation at depths
 exceeding 1 000 m;

Technical Notes:

- 1. 'Piezoelectric polymer film' sensing elements consist of polarized polymer film that is stretched over and attached to a supporting frame or spool (mandrel).
- 2. 'Flexible piezoelectric composite'
 sensing elements consist of piezoelectric
 ceramic particles or fibres combined with
 an electrically insulating, acoustically
 transparent rubber, polymer or epoxy
 compound, where the compound is an
 integral part of the sensing elements.
- 3. Hydrophone sensitivity is defined as twenty times the logarithm to the base 10 of the ratio of rms output voltage to a 1 V rms reference, when the hydrophone sensor, without a pre-amplifier, is placed in a plane wave acoustic field with an rms pressure of 1 μPa. For example, a hydrophone of -160 dB (reference 1 V per μPa) would yield an

output voltage of 10^{-8} V in such a field, while one of -180 dB sensitivity would yield only 10^{-9} V output. Thus, -160 dB is better than -180 dB.";

(ii) in 6A002(a), by repealing the Note and substituting -

"Note:

6A002(a) does not control germanium or silicon photodevices.

N.B.:

Silicon and other material based
'microbolometer' non-"space-qualified" "focal
plane arrays" are only controlled by

6A002(a)(3)(f).";

- (iii) in 6A002(a)(3) -
 - (A) by adding before the Technical Notes "N.B.:

Silicon and other material based
'microbolometer' non-"space-qualified"
"focal plane arrays" are only controlled
by 6A002(a)(3)(f).";

- (B) by repealing Note 2(a);
- (C) by renumbering Note 2(b) and Note 2(c) as

 Note 2(a) and Note 2(b) respectively;

(D) by adding at the end of 6A002(a)(3)(c) - "N.B.:

Silicon and other material based
'microbolometer' non-"space-qualified"
"focal plane arrays" are only controlled
by 6A002(a)(3)(f).";

(E) by adding -

"(f) Non-"space-qualified" non-linear (2-dimensional) infrared "focal plane arrays" based on 'microbolometer' material having individual elements with an unfiltered response in the wavelength range equal to or exceeding 8 000 nm but not exceeding 14 000 nm;

Technical Note:

For the purposes of 6A002(a)(3)(f),

'microbolometer' is defined as a

thermal imaging detector that, as a

result of a temperature change in

the detector caused by the

absorption of infrared radiation, is

used to generate any usable signal.";

- (iv) by repealing 6A003(b)(4) and substituting -
 - "(4) Imaging cameras incorporating "focal
 plane arrays" having any of the following:
 - (a) Incorporating "focal plane arrays" controlled by 6A002(a)(3)(a) to 6A002(a)(3)(e); or
 - (b) Incorporating "focal plane arrays"
 controlled by 6A002(a)(3)(f);

Notes:

- 1. Imaging cameras described in 6A003(b)(4) include "focal plane arrays" combined with sufficient "signal processing" electronics, beyond the read out integrated circuit, to enable as a minimum the output of an analogue or digital signal once power is supplied.
- 2. 6A003(b)(4)(a) does not control
 imaging cameras incorporating linear
 "focal plane arrays" with twelve
 elements or fewer, not employing
 time-delay-and-integration within
 the element, designed for any of the
 following:

Page 55

- (a) Industrial or civilian intrusion alarm, traffic or industrial movement control or counting systems;
- (b) Industrial equipment used for inspection or monitoring of heat flows in buildings, equipment or industrial processes;
- (c) Industrial equipment used for inspection, sorting or analysis of the properties of materials;
- (d) Equipment specially designed
 for laboratory use; or
- (e) Medical equipment.
- 3. 6A003(b)(4)(b) does not control imaging cameras having any of the following characteristics:
 - (a) A maximum frame rate equal to or less than 9 Hz;
 - (b) Having all of the following:
 - (1) Having a minimum
 horizontal or vertical
 Instantaneous-Field-of View (IFOV) of at least 10
 mrad/pixel (milliradians/

pixel);

- (2) Incorporating a fixed
 focal-length lens that is
 not designed to be removed;
- (3) Not incorporating a
 'direct view' display; and
 Technical Note:

'Direct view' refers to an imaging camera operating in the infrared spectrum that presents a visual image to a human observer using a near-to-eye micro display incorporating any light-security mechanism.

- (4) Having any of the
 following:
 - (a) No facility to obtain
 a viewable image of
 the detected field of-view;
 - (b) The camera is
 designed for a single
 kind of application
 and designed not to
 be user modified; or

Technical Note:

Instantaneous-Fieldof-View (IFOV) specified in Note 3(b) is the lesser figure of the Horizontal FOV or the Vertical FOV. Horizontal IFOV = horizontal Field of View (FOV) / number of horizontal detector elements; Vertical IFOV = vertical Field of View (FOV) / number of vertical detector elements;

specially designed
for installation into
a civilian passenger
land vehicle of less
than three tonnes
(gross vehicle weight)
and having all of the
following:

- (1) Is only operable
 when installed
 in any of the
 following:
 - (a) The
 civilian
 passenger
 land
 vehicle for
 which it
 was
 intended;
 or
 - (b) A specially
 designed,
 authorized
 maintenance
 test
 facility;
 and
- (2) Incorporates an active mechanism that forces the camera not to function when it is removed from

the vehicle for
which it was
intended;";

Note:

6A006 does not control instruments specially designed for fishery applications or biomagnetic measurements for medical diagnostics.

- (a) "Magnetometers" and subsystems,
 as follows:
 - - (a) SQUID systems
 designed for
 stationary operation,
 without specially
 designed subsystems

designed to reduce
in-motion noise, and
having a "noise
level" (sensitivity)
equal to or lower
(better) than 50 fT
(rms) per square root
Hz at a frequency of
1 Hz; or

- (b) SQUID systems having
 an in-motion "magnetometer" "noise
 level" (sensitivity)
 lower (better) than
 20 pT (rms) per
 square root Hz at a
 frequency of 1 Hz and
 specially designed to
 reduce in-motion
 noise;
- (2) Using optically pumped or
 nuclear precession
 (proton/Overhauser)
 "technology" having a
 "noise level" (sensitivity)
 lower (better) than 20 pT

(rms) per square root Hz;

- (3) Using fluxgate
 "technology" having a
 "noise level" (sensitivity)
 equal to or lower (better)
 than 10 pT (rms) per
 square root Hz at a
 frequency of 1 Hz;
- (4) Induction coil
 "magnetometers" having a
 "noise level" (sensitivity)
 lower (better) than any of
 the following:
 - (a) 0.05 nT (rms)/square
 root Hz at
 frequencies of less
 than 1 Hz;

- "magnetometers" having a
 "noise level" (sensitivity)
 lower (better) than 1 nT
 (rms) per square root Hz;
- (b) Underwater electric field
 sensors having a "noise level"
 (sensitivity) lower (better)
 than 8 nanovolt per meter per
 square root Hz when measured at
 1 Hz;
- (c) "Magnetic gradiometers", as
 follows:
 - (1) "Magnetic gradiometers"

 using multiple

 "magnetometers" controlled

 by 6A006(a);
 - (2) Fibre optic "intrinsic
 magnetic gradiometers"
 having a magnetic gradient
 field "noise level"
 (sensitivity) lower
 (better) than 0.3 nT/m
 (rms) per square root Hz;

- (3) "Intrinsic magnetic
 gradiometers", using
 "technology" other than
 fibre-optic "technology",
 having a magnetic gradient
 field "noise level"
 (sensitivity) lower
 (better) than 0.015 nT/m
 (rms) per square root Hz;
- (d) Compensation systems for
 magnetic or underwater electric
 field sensors resulting in a
 performance equal to or better
 than the control parameters of
 6A006(a), 6A006(b) or
 6A006(c);";
- (vi) in 6A102, by repealing "specified in" and substituting "controlled by";
- (vii) in 6A108 -
 - (A) in 6A108(a), by adding ", "unmanned
 aerial vehicles" controlled by 9A012"
 after "9A004";
 - (B) in 6A108(b), by repealing "missiles" or unmanned aerial vehicles specified in 9A012" and substituting "missiles'";

- (C) in 6A108(b)(2), by adding at the end "Technical Note:
 - In 6A108(b), 'missiles' means complete rocket systems and "unmanned aerial vehicle" systems capable of a range exceeding 300 km.";
- (viii) in 6A203(b), by repealing "specified in"
 wherever it appears and substituting
 "controlled by";
 - (ix) in 6A205, by repealing "specified in" and substituting "controlled by";
- (zg) in the Dual-use Goods List, in Category 6, in subcategory 6D -
 - (i) in 6D003(b) -
 - (A) in 6D003(b)(1), by adding "and electric field" before "compensation";
 - (B) in 6D003(b)(2), by adding "and electric field" after "magnetic";
 - (ii) in 6D103 -
 - (A) by repealing ""missiles" or unmanned
 aerial vehicles specified in 9A012" and
 substituting "'missiles'";
 - (B) by adding at the end "Technical Note:

In 6D103, 'missiles' means complete
rocket systems and "unmanned aerial

vehicle" systems capable of a range
exceeding 300 km.";

- (zh) in the Dual-use Goods List, in Category 6, in subcategory 6E, by repealing 6E003 and substituting "6E003 Other "technology", as follows:

See also 2E003(f).

- (2) Optical fabrication
 "technology" using single point
 diamond turning techniques to
 produce surface finish
 accuracies of better than 10 nm
 rms on non-planar surfaces
 exceeding 0.5 m²;
- (b) "Technology" "required" for the
 "development", "production" or "use"
 of specially designed diagnostic

instruments or targets in test

facilities for "SHPL" testing or

testing or evaluation of materials

irradiated by "SHPL" beams;";

- (zi) in the Dual-use Goods List, in Category 7, in subcategory 7A -
 - (i) in 7A002 -
 - (A) in 7A002(a), by repealing "three months"
 and substituting "one month";
 - (B) in 7A002(a)(1), by repealing "10" and substituting "12";
 - (C) in 7A002(a)(2), by repealing "10 g to
 100 g inclusive; or" and substituting
 "12 g to 100 g inclusive;";
 - (D) by renumbering 7A002(b) as 7A002(c);
 - (E) by adding -
 - "(b) An 'angle random walk' of less

 (better) than or equal to 0.0035

 degree per square root hour;

 Note:

7A002(b) does not control spinning mass gyros (spinning mass gyros are gyros which use a continually rotating mass to sense angular motion).

Technical Note:

For the purpose of 7A002(b), 'angle random walk' is the angular error build-up with time that is due to white noise in angular rate. (IEEE STD 528-2001);";

- (ii) by repealing 7A007;
- - (a) Linear accelerometers, designed
 for use in inertial navigation
 systems or in guidance systems
 of all types, usable in
 'missiles', and having all of
 the following characteristics,
 and specially designed
 components therefor:
 - (1) 'Scale factor'
 'repeatability' less
 (better) than 1 250 ppm;
 and

(2) 'Bias' 'repeatability'
less (better) than 1 250
micro g;

Technical Notes:

- (1) In 7A101(a), 'missiles'
 means complete rocket
 systems and "unmanned
 aerial vehicle" systems
 capable of a range
 exceeding 300 km.
- (2) 'Scale factor' is defined as the ratio of change in output to a change in the input.
- (3) The measurement of 'bias' and 'scale factor' refers to one sigma standard deviation with respect to a fixed calibration over a period of one year.
- (4) 'Repeatability' is defined according to IEEE Standard 528-2001 as follows: The closeness of agreement among repeated measurements of the same

variable under the same
operating conditions when
changes in conditions or
non-operating periods
occur between measurements.

Note:

7A101(a) does not control
accelerometers specially
designed and developed as
Measurement While Drilling (MWD)
sensors for use in downhole
well service operations.

- (b) Continuous output
 accelerometers specified to
 function at acceleration levels
 exceeding 100 g;";
- (iv) in 7A102 -
 - (A) by repealing ""missiles"" and
 substituting "'missiles'";
 - (B) by adding at the end "Technical Note:

In 7A102, 'missiles' means complete rocket systems and "unmanned aerial vehicle" systems capable of a range exceeding 300 km.";

- (v) in 7A103 -
 - (A) in 7A103(b), by repealing "unmanned
 aerial vehicles specified in" and
 substituting ""unmanned aerial vehicles"
 controlled by";
 - (B) by repealing 7A103(c) and substituting -
 - "(c) 'Integrated navigation systems',

 designed or modified for 'missiles'

 and capable of providing a

 navigational accuracy of 200 m

 "Circle of Equal Probability" (CEP)

 or less;

Technical Note:

- (1) An 'integrated navigation
 system' typically incorporates
 the following components:
 - (a) An inertial measurement
 device (e.g. an attitude
 and heading reference
 system, inertial reference
 unit, or inertial
 navigation system);
 - (b) One or more external
 sensors used to update the
 position or velocity or
 both, either periodically

or continuously throughout
the flight (e.g. satellite
navigation receiver, radar
altimeter, or Doppler
radar); and

- (c) Integration hardware and software.
- (2) In 7A103(c), 'missiles' means
 complete rocket systems and
 "unmanned aerial vehicle"
 systems capable of a range
 exceeding 300 km.";
- (vi) in 7A105 -
 - (A) in 7A105(a), by repealing "specified in 9A004, unmanned aerial vehicles specified in 9A012 or sounding rockets specified in" and substituting "controlled by 9A004, "unmanned aerial vehicles" controlled by 9A012 or sounding rockets controlled by";
 - (B) in 7A105(b), by repealing "(1 165 nautical miles/hour)";
- (vii) in 7A106, by repealing ", unmanned aerial
 vehicles specified in 9A012";
- (viii) in 7A115, by repealing ", unmanned aerial
 vehicles specified in 9A012";

- (ix) in 7A116 -
 - (A) by repealing ", unmanned aerial vehicles specified in 9A012";
 - (B) in 7A116(c), by repealing "specified in"
 and substituting "controlled by";
 - (C) in 7A116(c), by repealing "of more than"
 and substituting "greater than";
- (zj) in the Dual-use Goods List, in Category 7, in subcategory 7B, in 7B103 -
 - (i) in 7B103(a), by repealing "specified in" and substituting "controlled by";
 - (ii) in 7B103(b), by repealing "specified in" where
 it twice appears and substituting "controlled
 by";
- (zk) in the Dual-use Goods List, in Category 7, in subcategory 7D -
 - (i) in 7D101, by repealing "specified in" and substituting "controlled by";
 - (ii) in 7D102, by repealing "specified in" wherever it appears and substituting "controlled by";
 - (iii) in 7D103, by repealing "unmanned aerial
 vehicles specified in" and substituting
 ""unmanned aerial vehicles" controlled by";
- (zl) in the Dual-use Goods List, in Category 7, in subcategory 7E, in 7E101, by repealing "specified in" and substituting "controlled by";

- (zm) in the Dual-use Goods List, in Category 8, in subcategory 8A, in 8A002 -
 - (i) in 8A002(f), by adding at the end "Note:
 - 8A002(f) does not control digital cameras specially designed for consumer purposes, other than those employing electronic image multiplication techniques.";
 - (ii) in 8A002(h), by repealing ""stored programme
 controlled"";
 - (iii) in 8A002(i)(2), by repealing ""stored programme controlled"" where it twice appears;
- (zn) in the Dual-use Goods List, in Category 9, in subcategory 9A -

N.B.:

See also 9A101.

(a) Incorporating any of the
 technologies controlled by
9E003(a); or

Note:

9A001(a) does not control aero gas turbine engines which meet all of the following:

- 1. Certified by the civil
 aviation authority in a
 "Participating State"; and
- 2. Intended to power nonmilitary manned "aircraft"
 for which one of the
 following has been issued
 by a "Participating State"
 for the "aircraft" with
 this specific engine type:
 - (a) A civil Type

 Certificate; or
 - (b) An equivalent
 document recognized
 by the International
 Civil Aviation
 Organisation (ICAO).
- (b) Designed to power an "aircraft"

 designed to cruise at Mach 1 or

 higher for more than 30

 minutes;";
- (ii) in 9A002, by repealing "Marine gas turbine
 engines" and substituting "'Marine gas turbine
 engines'";

- (iii) by repealing 9A012 and substituting -
 - "9A012 "Unmanned Aerial Vehicles" ("UAVs"),
 associated systems, equipment and
 components as follows:
 - (a) "UAVs" having any of the
 following:
 - (1) An autonomous flight
 control and navigation
 capability (e.g. an
 autopilot with an Inertial
 Navigation System); or
 - (2) Capability of controlled
 flight out of the direct
 visual range involving a
 human operator (e.g.,
 televisual remote control);
 - (b) Associated systems, equipment
 and components as follows:
 - (1) Equipment specially
 designed for remotely
 controlling the "UAVs"
 controlled by 9A012(a);
 - (2) Guidance or control
 systems, other than those
 controlled in Category 7,
 specially designed for

- integration into "UAVs"
 controlled by 9A012(a);
- (3) Equipment and components
 specially designed to
 convert a manned
 "aircraft" to a "UAV"
 controlled by 9A012(a);

Note:

9A012 does not control model
aircraft.";

- (iv) in 9A101, by repealing "usable in "missiles"";
 - (v) in 9A105(b), by repealing "specified in" and substituting "controlled by";
- (vi) in 9A106 -
 - (A) in 9A106(d), by repealing "of more than"
 and substituting "greater than";
 - (B) in Note (a) to 9A106(d), by repealing "of 24 litres per minute or greater, at an absolute pressure of 7 MPa or greater" and substituting "equal to or greater than 24 litres per minute, at an absolute pressure equal to or greater than 7 MPa";
 - (C) by adding -

- "(e) Liquid propellant tanks specially designed for propellants controlled by 1C111, or other liquid propellants used in the systems controlled by 9A004 or 9A104;";
- (vii) in 9A107, by repealing "of 0.841 MNs or greater" and substituting "equal to or greater than $8.41 \times 10^5 \, \text{Ns}$ ";
- (viii) by repealing 9A109 and substituting "9A109 Hybrid rocket motors, usable in
 'missiles', other than those
 controlled by 9A009, and specially
 designed components therefor;
 Technical Note:

In 9A109, 'missiles' means complete rocket systems and "unmanned aerial vehicle" systems capable of a range exceeding 300 km.

N.B.:

See also 9A119.";

- (ix) in 9A110, by repealing "specified in" wherever
 it appears and substituting "controlled by";
 - (x) in 9A115 -

- (A) in 9A115(a), by repealing "specified in 9A004, unmanned aerial vehicles specified in 9A012 or sounding rockets specified in" and substituting "controlled by 9A004, "unmanned aerial vehicles" controlled by 9A012 or sounding rockets controlled by";
- (B) in 9A115(b), by repealing "specified in 9A004 or sounding rockets specified in" and substituting "controlled by 9A004, "unmanned aerial vehicles" controlled by 9A012 or sounding rockets controlled by";
- (xi) by adding -
 - "9A350 Spraying or fogging systems,

 specially designed or modified for

 fitting to "aircraft", "lighter
 than-air vehicles" or "unmanned

 aerial vehicles" controlled by 9A012,

 and specially designed components

 therefor, as follows:
 - (a) Complete spraying or fogging systems capable of delivering, from a liquid suspension, an initial droplet the 'VMD' of which is less than 50 microns at a flow rate of greater than two litres per minute;

- (b) Spray booms or arrays of
 'aerosol generating units'
 capable of delivering, from a
 liquid suspension, an initial
 droplet the 'VMD' of which is
 less than 50 microns at a flow
 rate of greater than two litres
 per minute;
- (c) 'Aerosol generating units'
 specially designed for fitting
 to systems controlled by
 9A350(a) and 9A350(b);

Notes:

- 1. 'Aerosol generating units' are devices specially designed or modified for fitting to "aircraft" such as nozzles, rotary drum atomizers and similar devices.
- 2. 9A350 does not control spraying or fogging systems and components that are demonstrated not to be capable of delivering biological agents in the form of infectious aerosols.

Technical Notes:

- 1. Droplet size for spray
 equipment or nozzles specially
 designed for use on "aircraft",
 "lighter-than-air vehicles" or
 "unmanned aerial vehicles"
 controlled by 9A012 should be
 measured using either of the
 following:
 - (a) Doppler laser method;
 - (b) Forward laser diffraction
 method.
- 2. In 9A350, 'VMD' means Volume Median Diameter and, for waterbased system, this equates to Mass Median Diameter (MMD).";
- (zo) in the Dual-use Goods List, in Category 9, in subcategory 9B -
 - (i) by adding -
 - "9B010 Equipment specially designed for the "production" of "UAVs" and associated systems, equipment and components controlled by 9A012;";
 - (ii) in 9B106 -
 - (A) in 9B106(a)(1), by repealing "of 10 g rms or greater between 20 Hz and 2 000 Hz and

- imparting forces of 5 kN or greater" and substituting "equal to or greater than 10 g rms, measured 'bare table', between 20 Hz and 2 kHz imparting forces equal to or greater than 5 kN";
- (B) in 9B106(a)(2), by repealing "of 15 000 m
 or greater" and substituting "equal to or
 greater than 15 km";
- (C) in 9B106(a), by adding at the end "Technical Note:
 - 9B106(a) describes systems that are capable of generating a vibration environment with a single wave (e.g., a sine wave) and systems capable of generating a broadband random vibration (i.e. power spectrum).";
- (D) in 9B106(b), by repealing "Anechoic" and substituting "Environmental";
- (E) in 9B106(b)(1), by repealing "(referenced to 20 micropascals) or with a rated power output of 4 kW or greater" and substituting "(referenced to 2 x 10⁻⁵ N/m²) or with a total rated acoustic power output of 4 kW or greater";
- (F) in 9B106(b)(2), by repealing "of 15 000 m
 or greater" and substituting "equal to or

greater than 15 km";

(G) by adding at the end - "Note:

In 9B106, 'bare table' means a flat table, or surface, with no fixture or fittings.";

(iii) in 9B117 -

- (A) by repealing "rockets or rocket motors"
 and substituting "rockets, motors or
 engines";
- (B) in 9B117(a), by repealing "The capacity to handle more than 90 kN of thrust" and substituting "The capacity to handle solid or liquid propellant rockets, motors or engines having a thrust greater than 90 kN";
- (zp) in the Dual-use Goods List, in Category 9, in subcategory 9C, in 9C110, by repealing "specified in"
 where it twice appears and substituting "controlled
 by";
- (zq) in the Dual-use Goods List, in Category 9, in subcategory 9D -
 - (i) in 9D004, by adding -
 - "(e) "Software" specially designed or modified for the "use" of "UAVs" and associated systems, equipment and components controlled by 9A012;";

- (ii) in 9D103, by adding ", "unmanned aerial
 vehicles" controlled by 9A012" after "9A004";
- - (iv) in 9D105, by repealing "specified in 9A004 or sounding rockets specified in" and substituting "controlled by 9A004, "unmanned aerial vehicles" controlled by 9A012 or sounding rockets controlled by";
- (zr) in the Dual-use Goods List, in Category 9, in subcategory 9E -
 - (i) in 9E001, by repealing "9A011" and substituting "9A012";
 - (ii) by repealing 9E003(a)(11) and substituting "(11) Hollow fan blades;";
 - (iii) in 9E102, by adding ""unmanned aerial
 vehicles" controlled by 9A012" after "9A004,";
- (zs) in the Definitions of Terms -
 - (i) in the definition of "Allocated by the ITU", by repealing "ITU Radio Regulations (Edition 1998)" and substituting "current edition of the ITU Radio Regulations";
 - (ii) in the definition of "Electronic assemblies",
 by repealing "3 4 5" and substituting "2 3 4
 5";
 - (iii) in the definition of "Real time bandwidth", by

- repealing "Real time" and substituting "Realtime";
- (iv) by repealing the definition of "Riot control
 agents" and substituting -

"ML7 "Riot control agents" (暴動控制劑)

Substances which, under the expected conditions of use for riot control purposes, produce rapidly in humans sensory irritation or disabling physical effects which disappear within a short time following termination of exposure. (Tear gases are a subset of "riot control agents".)";

- (v) by repealing the definition of "Stored
 programme controlled";
- (vi) by repealing the definition of "Tear gases";
- (vii) in the definition of "Technology", by
 repealing "Controlled "technology" is defined
 in the General Technology Note and in the
 Dual-Use Goods List" and substituting
 "Controlled "technology" for the Dual-Use
 Goods List is defined in the General
 Technology Note and in the Dual-Use Goods List.

Controlled "technology" for the Munitions List is specified in ML22";

- - (ix) by adding -

"ML10 "Lighter-than-air vehicles" (輕於空氣 載具)

Balloons and airships that rely on hot air or on lighter-than-air gases such as helium or hydrogen for their lift.

5 "Quantum cryptography" (量子密碼技術)

A family of techniques for the establishment of a shared key for "cryptography" by measuring the quantum-mechanical properties of a physical system (including those physical properties explicitly governed by quantum optics, quantum field theory, or quantum electrodynamics).

9 "Unmanned aerial vehicle" ("UAV") (無人駕駛飛行載具)

Any "aircraft" capable of initiating flight and

sustaining controlled flight and navigation without any human presence on board.".

Director-General of Trade and Industry

25 April 2006

Explanatory Note

This Order revises Schedule 1 to the Import and Export (Strategic Commodities) Regulations (Cap. 60 sub. leg. G) to reflect the latest changes in the control lists of strategic commodities adopted by various international non-proliferation regimes.

IMPORT AND EXPORT (STRATEGIC COMMODITIES) REGULATIONS (AMENDMENT OF SCHEDULE 1) ORDER 2006

ECONOMIC IMPLICATIONS

ECONOMIC IMPLICATIONS

The Order will facilitate the trade by removing outdated restrictions on trade in strategic commodities. In particular, the removal of control over microprocessors that have multiple data or instruction bus or serial communication ports will relieve the trade from the burden of applying for import and export licences for such commonly traded products. The relaxation of the control thresholds for digital computers will also be welcomed by the trade. On the other hand, the imposition of new controls should not have significant effects on general traders as the items concerned are not commonly traded by the importers and exporters of Hong Kong.