## L.N. 233 of 2009

# AIR POLLUTION CONTROL (MOTOR VEHICLE FUEL) (AMENDMENT) REGULATION 2009

# **CONTENTS**

Section		Page
1.	Commencement	B2937
2.	Interpretation	B2937
3.	Supplying or selling leaded petrol	B2939
4.	Supplying or selling fuel additives containing lead	B2939
5.	Dispensing of fuel additives containing lead	B2939
6.	Part V added	
	PART V	
	Motor Vehicle Biodiesel	
	10. Supplying or selling motor vehicle biodiesel	B2939
	11. Requirement to carry label for supplying or selling motor vehicle biodiesel	B2941
	12. Requirement as to statement of ester content on motor vehicle biodiesel label	B2943
7.	Schedules 3 and 4 added	
	Schedule 3 Specifications of Pure Motor Vehicle Biodiesel	B2945
	Schedule 4 Specifications of Motor Vehicle Biodiesel Label	B2949

# AIR POLLUTION CONTROL (MOTOR VEHICLE FUEL) (AMENDMENT) REGULATION 2009

(Made by the Secretary for the Environment under section 43 of the Air Pollution Control Ordinance (Cap. 311) after consultation with the Advisory Council on the Environment)

#### 1. Commencement

This Regulation comes into operation on 1 July 2010.

# 2. Interpretation

Section 2 of the Air Pollution Control (Motor Vehicle Fuel) Regulation (Cap. 311 sub. leg. L) is amended by adding—

- ""biodiesel" (生化柴油) means a fuel comprising mono-alkyl esters of long chain fatty acids derived from vegetable oils or animal fats;
  - "ester content" (酯含量) means the content of fatty acid methyl ester in a fuel determined by—
    - (a) if the fuel is pure motor vehicle biodiesel, the test procedure of the European Standards commonly known as EN 14103:2003; or
    - (b) if the fuel is motor vehicle biodiesel blend, the test procedure of the European Standards commonly known as EN 14078:2003:
  - "motor vehicle biodiesel" (汽車生化柴油) means pure motor vehicle biodiesel or motor vehicle biodiesel blend;
  - "motor vehicle biodiesel blend" (汽車生化柴油混合物) means a motor vehicle fuel that must be blended only from pure motor vehicle biodiesel and motor vehicle diesel;
  - "motor vehicle biodiesel dispenser" (汽車生化柴油加油機) means an installation used or intended to be used for dispensing motor vehicle biodiesel into the fuel tank of a motor vehicle (whether or not also for dispensing motor vehicle biodiesel into any other container);
  - "motor vehicle biodiesel label" (汽車生化柴油標籤) means a label that complies with the specifications as specified in Schedule 4;
  - "motor vehicle biodiesel retailer" (汽車生化柴油零售商) means a person who sells, or offers for sale, motor vehicle biodiesel by retail to the public at large for use in motor vehicles;

- "motor vehicle biodiesel supplier" (汽車生化柴油供應商) means a person who, in the course of business, supplies or distributes motor vehicle biodiesel but does not include a motor vehicle biodiesel retailer;
- "motor vehicle fuel" (汽車燃料) means any fuel that is used in the propulsion of a motor vehicle;
- "pure motor vehicle biodiesel" (純汽車生化柴油) means any motor vehicle fuel that complies with the specifications as specified in Schedule 3;".

#### 3. Supplying or selling leaded petrol

- (1) Section 3(3) is amended by repealing "until the contrary is proved" and substituting "unless there is evidence to the contrary".
- (2) Section 3(4) is amended by repealing "until the contrary is proved" and substituting "unless there is evidence to the contrary".

# 4. Supplying or selling fuel additives containing lead

- (1) Section 8(3) is amended by repealing "until the contrary is proved" and substituting "unless there is evidence to the contrary".
- (2) Section 8(4) is amended by repealing "until the contrary is proved" and substituting "unless there is evidence to the contrary".

# 5. Dispensing of fuel additives containing lead

Section 9(2) is amended by repealing "until the contrary is proved" and substituting "unless there is evidence to the contrary".

#### 6. Part V added

The following is added—

#### "PART V

#### MOTOR VEHICLE BIODIESEL

# 10. Supplying or selling motor vehicle biodiesel

(1) Any motor vehicle biodiesel supplier who knowingly supplies or distributes any substance (that is not motor vehicle biodiesel) as motor vehicle biodiesel commits an offence and is liable to a fine at level 5.

- (2) Subject to subsection (5), any motor vehicle biodiesel retailer who knowingly sells or offers for sale any substance (that is not motor vehicle biodiesel) as motor vehicle biodiesel commits an offence and is liable to a fine at level 5.
- (3) For the purposes of any proceedings under subsection (1), the person charged is, unless there is evidence to the contrary, presumed to have known that the substance the person supplied or distributed was not motor vehicle biodiesel.
- (4) For the purposes of any proceedings under subsection (2), the person charged is, unless there is evidence to the contrary, presumed to have known that the substance the person sold or offered for sale was not motor vehicle biodiesel.
- (5) A motor vehicle biodiesel retailer does not commit an offence under subsection (2) if the retailer proves that—
  - (a) he or she purchased, or otherwise obtained, the substance with a warranty or other written evidence from the motor vehicle biodiesel supplier who supplied or distributed the substance that the substance was motor vehicle biodiesel; and
  - (b) at the time of the alleged offence, the substance was in the same state as it was in at the time of delivery to him or her.

# 11. Requirement to carry label for supplying or selling motor vehicle biodiesel

- (1) Any person who knowingly supplies, distributes, sells or offers for sale any motor vehicle biodiesel containing an ester content over 5% through a motor vehicle biodiesel dispenser must display prominently on the dispenser a motor vehicle biodiesel label.
- (2) A person who fails to comply with subsection (1) commits an offence and is liable to a fine at level 5.
- (3) Any person who knowingly supplies, distributes, sells or offers for sale any motor vehicle biodiesel containing an ester content over 5% in any container other than a motor vehicle biodiesel dispenser must ensure that a motor vehicle biodiesel label that complies with the requirements specified in subsection (4) is securely affixed to or printed on the container.
- (4) The requirements mentioned in subsection (3) are the following—

- (a) if the container is in the form of a packet, the label must appear on one of the largest surfaces of the packet and the size of the label must be proportionally scaled so that it covers at least 40% of the area of the surface on which it appears;
- (b) if the container is in the form of a tin or drum, the label must appear on the curved surface of the tin or drum and the size of the label must be proportionally scaled so that it covers at least 20% of the area of the curved surface on which it appears; or
- (c) if the container is in any other form, the size of the label must be proportionally scaled so that it covers at least 40% of the area of the surface on which it appears.
- (5) A person who fails to comply with subsection (3) commits an offence and is liable to a fine at level 5.
- (6) For the purposes of any proceedings under subsection (2) or (5), the person charged is, unless there is evidence to the contrary, presumed to have known the ester content of the motor vehicle biodiesel that the person supplied, distributed, sold or offered for sale.

# 12. Requirement as to statement of ester content on motor vehicle biodiesel label

- (1) Any motor vehicle biodiesel supplier who knowingly supplies or distributes any motor vehicle biodiesel containing an ester content that is more than 1% higher or lower than the percentage of ester content as indicated on the motor vehicle biodiesel label commits an offence and is liable to a fine at level 5.
- (2) Subject to subsection (5), any motor vehicle biodiesel retailer who knowingly sells or offers for sale any motor vehicle biodiesel containing an ester content that is more than 1% higher or lower than the percentage of ester content as indicated on the motor vehicle biodiesel label commits an offence and is liable to a fine at level 5.
- (3) For the purposes of any proceedings under subsection (1), the person charged is, unless there is evidence to the contrary, presumed to have known the ester content of the motor vehicle biodiesel that the person supplied or distributed.
- (4) For the purposes of any proceedings under subsection (2), the person charged is, unless there is evidence to the contrary, presumed to have known the ester content of the motor vehicle biodiesel that the person sold or offered for sale.
- (5) A motor vehicle biodiesel retailer does not commit an offence under subsection (2) if the retailer proves that—

- (a) he or she purchased, or otherwise obtained, the motor vehicle biodiesel with a warranty or other written evidence from the motor vehicle biodiesel supplier who supplied or distributed the motor vehicle biodiesel that the motor vehicle biodiesel contained an ester content of the percentage as indicated on the motor vehicle biodiesel label; and
- (b) at the time of the alleged offence, the motor vehicle biodiesel was in the same state as it was in at the time of delivery to him or her.".

#### 7. Schedules 3 and 4 added

The following are added—

#### "SCHEDULE 3

[s. 2]

#### Specifications of Pure Motor Vehicle Biodiesel

Any pure motor vehicle biodiesel must—

- (a) contain not less than 96.5% by mass of fatty acid methyl ester as determined by EN 14103:2003 (the addition of components that are not fatty acid methyl ester, other than an additive, is not allowed);
- (b) have a density at 15°C of not lower than 860 kg/m³ and not higher than 900 kg/m³ as determined by EN ISO 3675:1998;
- (c) have a viscosity at 40°C of not lower than 3.50 mm<sup>2</sup>/s and not higher than 5.00 mm<sup>2</sup>/s as determined by EN ISO 3104:1996;
- (d) have a flash point of above 101°C as determined by EN ISO 3679:2004;
- (e) contain not more than 10.0 mg/kg of sulphur as determined by EN ISO 20884:2004;
- (f) contain not more than 0.30% by mass of carbon residue (on 10% distillation residue) as determined by EN ISO 10370:1995;
- (g) have a cetane number of not less than 51.0 as determined by EN ISO 5165:1998;
- (h) contain not more than 0.02% by mass of sulphated ash as determined by ISO 3987:1994;
- (i) contain not more than 500 mg/kg of water as determined by EN ISO 12937:2000;

- (*j*) contain not more than 24 mg/kg of total contamination as determined by EN 12662:2008;
- (k) have a copper strip corrosion (for 3 hours at 50°C) rating of Class 1 as determined by EN ISO 2160:1998;
- (l) have an oxidation stability at 110°C of not lower than 6 hours as determined by EN 14112:2003;
- (m) have an acid value of not more than 0.50 mg KOH/g as determined by EN 14104:2003;
- (n) have an iodine value of not more than 120 g iodine/100 g as determined by EN 14111:2003;
- (o) contain not more than 12.0% by mass of linolenic acid methyl ester as determined by EN 14103:2003;
- (p) contain not more than 1% by mass of polyunsaturated (greater than or equal to 4 double bonds) methyl esters;
- (q) contain not more than 0.20% by mass of methanol content as determined by EN 14110:2003;
- (r) contain not more than 0.80% by mass of monoglyceride content as determined by EN 14105:2003;
- (s) contain not more than 0.20% by mass of diglyceride content as determined by EN 14105:2003;
- (t) contain not more than 0.20% by mass of triglyceride content as determined by EN 14105:2003;
- (u) contain not more than 0.02% by mass of free glycerol as determined by EN 14105:2003;
- (v) contain not more than 0.25% by mass of total glycerol as determined by EN 14105:2003;
- (w) contain not more than 5.0 mg/kg of Group I metals (sodium plus potassium) as determined by EN 14538:2006;
- (x) contain not more than 5.0 mg/kg of Group II metals (calcium plus magnesium) as determined by EN 14538:2006; and
- (y) contain not more than 4.0 mg/kg of phosphorus content as determined by EN 14107:2003.

### Note: In this Schedule—

- "EN" followed by a numerical symbol ("EN number") means the test procedures of the European Standards commonly known by that EN number;
- "ISO" followed by a numerical symbol ("ISO number") means the test procedures of the International Organization for Standardization commonly known by that ISO number.

#### SCHEDULE 4

[s. 2]

#### SPECIFICATIONS OF MOTOR VEHICLE BIODIESEL LABEL

1. The design of the label must be as specified in the diagram below—

# 汽車生化柴油 Motor Vehicle Biodiesel

本 (i) 的酯含量為 (ii)%\*
This (iii) contains (iv)% of ester content\*

不適合某些車輛

Not suitable for some vehicles

使用前請諮詢有關的認可車輛代理商

Consult the relevant authorized vehicle dealers before use

本汽車生化柴油為《空氣污染管制(汽車燃料)規例》(第311章,附屬法例 L)所指的汽車生化柴油。

This motor vehicle biodiesel is the motor vehicle biodiesel within the meaning of the Air Pollution Control (Motor Vehicle Fuel) Regulation (Cap. 311 sub. leg. L).

- \* 實際酯含量與本標籤所示的含量,相差不多於1%。
- \* The actual ester content does not deviate by more than 1% from the content shown on this label.
- 2. The label must be rectangular in shape and must have a minimum size of 60 cm wide and 45 cm high and surrounded by a black line as demarcation.
- 3. The background colour of the label must be yellow.
- 4. For the Chinese text, all characters and numbers, except otherwise specified in paragraph 6 below, must be printed in black, "標楷體" Bold typeface and 24 mm high font size.
- 5. For the English text, all letters and numbers must be printed in black, Arial typeface and 25 mm high font size.
- 6. The characters "不適合某些車輛" and "使用前請諮詢有關的認可車輛代理商" must be printed in red, "標楷體" Bold typeface and 24 mm high font size.
- 7. The spaces marked by (i) and (iii) must be printed with—

- (a) if the motor vehicle biodiesel is pure motor vehicle biodiesel, the characters "純汽車生化柴油" and the letters "pure motor vehicle biodiesel" respectively; or
- (b) if the motor vehicle biodiesel is motor vehicle biodiesel blend, the characters "汽車生化柴油混合物" and the letters "motor vehicle biodiesel blend" respectively.
- 8. The spaces marked by (ii) and (iv) must be printed with a number representing the proportion in percentage of the ester content in the motor vehicle biodiesel determined by—
  - (a) if the motor vehicle biodiesel is pure motor vehicle biodiesel, the test procedure of the European Standards commonly known as EN 14103:2003; or
  - (b) if the motor vehicle biodiesel is motor vehicle biodiesel blend, the test procedure of the European Standards commonly known as EN 14078:2003.".

Edward YAU
Secretary for the Environment

12 November 2009

# **Explanatory Note**

This Regulation amends the Air Pollution Control (Motor Vehicle Fuel) Regulation (Cap. 311 sub. leg. L) ("the principal Regulation"). The main purpose is to provide for the specifications of biodiesel used as motor vehicle fuel so as to prevent adverse impact on the environment resulting from the use of substandard biodiesel for motor vehicles.

- 2. Section 2 provides for the definitions newly added.
- 3. Sections 3 to 5 amend sections 3, 8 and 9 of the principal Regulation respectively to make clear that the relevant provisions only impose an evidential burden on a person charged.
- 4. Section 6 adds to the principal Regulation a new Part V which provides for the regulatory control on the supply and sale of motor vehicle biodiesel and the labelling requirements.
- 5. Section 7 adds to the principal Regulation new Schedules 3 and 4. The new Schedule 3 sets out the specifications of the pure motor vehicle biodiesel while the new Schedule 4 sets out the specifications of the motor vehicle biodiesel label.